


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County SEDGWICK	Fraction NW 3/4 SE 1/4	Section number 8	Township number T 27	Range number S 1W E/W
2. Distance and direction from nearest town or city: Street address of well location if in city:		1662 MURRY WICHITA KANS		3. Owner of well: MERLE NEAGLE R.R. or street: 1662 MURRY City, state, zip code: WICHITA KANS 67212		
4. Locate with "X" in section below: 		Sketch map: BORED 9" HOLE TO 13 FT. THEN 6 INCH TO 28 FT - USED SAND BUCKET TO COMPLETION A 45 FT.		6. Bore hole dia. 9 in. Completion date 3-21-78 Well depth 45 ft.		
5. Type and color of material		From		To		7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary
TOP SOIL BLACK		0		3		8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☒ Lawn ☐ Oil field water ☐ Other
CLAY RED		3		12		9. Casing: Material RMP Height: 9 ft. or below Threaded 3/4 Welded ☒ Surface 7 in. RMP 3/4 PVC ☐ Weight 1.55 lbs./ft. Dia. 5 in. to 45 ft. depth Wall Thickness: inches or Dia. 5 in. to 45 ft. depth gage No. 0.200
SANDY CLAY RED		12		19		10. Screen: Manufacturer's name J+L Type RMP Dia. 7 FT. Slot gauge 3/8 Length 7 FT. Set between 38 ft. and 45 ft. Gravel pack? NO Size range of material
SAND FINE YELLOWISH		19		26		11. Static water level: 28 ft. below land surface Date 3-21-78 mo./day/yr.
GRAVEL COARSE BROWN		26		28		12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 60 g.p.m.
SAND MEDIUM TAN		28		34		13. Water sample submitted: NO mo./day/yr. Yes ☒ No ☐ Date
CLAY GRAY		34		35		14. Well head completion: Pitless adapter 12 inches above grade
SAND COARSE TAN		35		45		15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 2 ft. to 13 ft.
						16. Nearest source of possible contamination: PLASTIC ft. 12 Direction N Type PLASTIC Well disinfected upon completion? Yes ☒ No ☐
						17. Pump: ☒ Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: ☐ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other
18. Elevation: 1300		19. Remarks: GRouted TO WITHIN 3 FT FROM SURFACE - CUSTOMER TO MAKE INSTALLATION OF PUMP PROBABLY USING ADAPTER		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP & WELL Business name 3142 MENTOR License No. 104 Address WICHITA Signature Alvin W. Bearden Date 4/4/78 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5