


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: SE 1/4 SE 1/4 NE 1/4 Section Number: 9 Township Number: T 27 S Range Number: R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

1736 Tony Ln

2 WATER WELL OWNER: Carr, Merle  
 RR#, St. Address, Box #: 1736 Tony Ln.  
 City, State, ZIP Code: Wichita KS 67212  
 Board of Agriculture, Division of Water Resources  
 Application Number: NA

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 52 ft. ELEVATION: 8-16-83

Depth(s) Groundwater Encountered 1. 24 ft. 2. 24 ft. 3. 24 ft.

WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 8-16-83

Pump test data: Well water was 24 ft. after 24 hours pumping 360 gpm

Est. Yield 9 gpm: Well water was 15 ft. after 10 hours pumping 360 gpm

Bore Hole Diameter 9 in. to 15 in. and 10 in. to 360 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X

Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X

7 Fiberglass Threaded X

Blank casing diameter 6 in. to 31 in. ft. Dia 5 in. to 44 in. ft. Dia 5 in. to 44 in. ft.

Casing height above land surface 31 in. weight 5 lbs./ft. Wall thickness or gauge No. 44

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 6" 31 ft. to 36 ft. From 5" 44 ft. to 52 ft.

GRAVEL PACK INTERVALS: From 6" 31 ft. to 36 ft. From 5" 44 ft. to 52 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 15 ft. From 3 ft. to 15 ft. From 3 ft. to 15 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? South How many feet? 40

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0 3 DARK BRN. Clay 0 3 DARK BRN. Clay

3 12 Reddish Brn. sand clay Lgam 3 12 Reddish Brn. sand clay Lgam

12 36 LT Tan fine Sand 12 36 LT Tan fine Sand

36 40 Gray Clay 36 40 Gray Clay

40 52 LT Brn med Sand 40 52 LT Brn med Sand

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-17-83 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 295 This Water Well Record was completed on (mo/day/yr)

under the business name of Protheroe Pump & Well Service by (signature) Sherry Protheroe

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top

three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL

OWNER and retain one for your records.

OFFICE USE ONLY

T

27

R

1

EW

SEC.

9

SE 1/4

SE 1/4

NE 1/4

1/4