

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 SW 1/4 NE 1/4	9	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1830 CRAMER, WICHITA KANS					
2 WATER WELL OWNER:		67212			
RR#, St. Address, Box # : WEST WOOD CONSTRUCTION		Board of Agriculture, Division of Water Resources			
City, State, ZIP Code DAN KOTD 1830 CRAMER WICHITA		Application Number: NONE			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 26 1/2 ft. ELEVATION: 1300			
		Depth(s) Groundwater Encountered 1. 16 1/2 ft. 2. NA ft. 3. NA ft.			
		WELL'S STATIC WATER LEVEL 16 1/2 ft. below Basement measured on mo/day/yr 5-1-86			
		Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield 35 gpm Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 9 in. to 10 ft. and 6 in. to 26 1/2 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply ☒ 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No ☒					
5 TYPE OF BLANK CASING USED:					
1 Steel		☒ 3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS ☒ Glued ☒ Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter 5 in. to 17 1/2 ft. Dia		7 Fiberglass	Threaded		
Casing height above Basement 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	☒ 7 PVC	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	☒ 8 RMP (SR)	11 Other (specify)
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot		☒ 3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS:		7 Torch cut 10 Other (specify)			
From 16 1/2 ft. to 26 1/2 ft.					
GRAVEL PACK INTERVALS:					
From NONE ft. to 18 ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 18 ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
☒ 3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? EAST		How many feet? 11 FT.			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	8	CLAY - RED			
8	12	SANDY CLAY RED			
12	18	SAND TAN MED			
18	26 1/2	SAND TAN COARSE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-1-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 6/12/86 under the business name of BEARDEN PUMP & WELL by (signature) Joe W Bearden					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4