


1 LOCATION OF WATER WELL: County: <u>Sedg.</u>		Fraction: <u>SE 1/4 NE 1/4 SE 1/4</u>	Section Number: <u>9</u>	Township Number: <u>T 27 S</u>	Range Number: <u>R 1 E W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>See Below</u>					
2 WATER WELL OWNER: <u>VERN FULKNER</u> RR#, St. Address, Box #: <u>1601 no Brunswick</u> City, State, ZIP Code: <u>WICHITA KS 67212</u>			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>50</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>16</u> ft. 2. <u>16</u> ft. 3. <u>16</u> ft. WELL'S STATIC WATER LEVEL <u>16</u> ft. below land surface measured on mo/day/yr <u>6-10-94</u> Pump test data: Well water was <u>16</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Est. Yield <u>50</u> gpm; Well water was <u>16</u> ft. after <u>12</u> hours pumping <u>20</u> gpm Bore Hole Diameter <u>11</u> in. to <u>50</u> ft., and <u>11</u> in. to <u>50</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No <u>X</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>5</u> in. to <u>40</u> ft. Dia. <u>2</u> in. to <u>40</u> ft. Dia. <u>2</u> in. to <u>40</u> ft. Dia. <u>2</u> in. to <u>40</u> ft. Dia. Casing height above land surface <u>12</u> in. weight <u>2-60</u> lbs./ft. Wall thickness or gauge No. <u>160 PVC</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>50</u> ft. From <u>40</u> ft. to <u>50</u> ft. From <u>40</u> ft. to <u>50</u> ft. From <u>40</u> ft. to <u>50</u> ft. GRAVEL PACK INTERVALS: From <u>16</u> ft. to <u>50</u> ft. From <u>16</u> ft. to <u>50</u> ft. From <u>16</u> ft. to <u>50</u> ft. From <u>16</u> ft. to <u>50</u> ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>3</u> ft. to <u>16</u> ft. From <u>3</u> ft. to <u>16</u> ft. From <u>3</u> ft. to <u>16</u> ft. From <u>3</u> ft. to <u>16</u> ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? <u>North</u> How many feet? <u>45</u>					
FROM		TO		LITHOLOGIC LOG	
FROM		TO		PLUGGING INTERVALS	
0 2		Top soil			
2 9		clay			
9 32		fine sand			
32 33		clay			
33 50		gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-10-94</u> and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. <u>1318</u> This Water Well Record was completed on (mo/day/yr) <u>6-14-94</u> under the business name of <u>Whinnings Dully Inc</u> by (signature) <u>[Signature]</u>					