


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SE 1/4 Section Number 10 Township Number 27 Range Number 1 E/W E
 County: Sedg. Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Sedg. Co. Park
 RR#, St. Address, Box #: 6501 W. 21st
 City, State, ZIP Code: Wichita KS 67203
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 52 ft. ELEVATION: 10-10-86
 Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.
 WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 10-10-86
 Pump test data: Well water was 16 ft. after 12 hours pumping 50 gpm
 Est. Yield 80 gpm: Well water was 16 ft. after 12 hours pumping 50 gpm
 Bore Hole Diameter 11 in. to 52 ft., and 52 ft. to 52 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) Rest Rooms
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 24 ft. Dia. 5 in. in. to 50 ft. Dia. 50 in. to 50 ft.
 Casing height above land surface 12 in., weight 1.5 lbs./ft. Wall thickness or gauge No. SDR-26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) Rest Rooms
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 5 Mill slot 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) Rest Rooms
 SCREEN-PERFORATED INTERVALS: From 24 ft. to 33 ft., From 33 ft. to 52 ft.
 From 50 ft. to 52 ft., From 52 ft. to 52 ft.
 GRAVEL PACK INTERVALS: From 17 ft. to 52 ft., From 52 ft. to 52 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 17 ft., From 17 ft. to 52 ft., From 52 ft. to 52 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? SE How many feet? 10

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	top soil			
2	18	fine sand			
18	19	clay			
19	33	sand			
33	34	clay			
34	48	fine sand			
48	49	clay			
49	52	sand med.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-10-86 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-10-86
 under the business name of Weninger Dwyer by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or block the correct answer. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4