


NW NW SE SE

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

Copy - HP

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction: 3/4 1/4 NE 1/4	Section Number: 11	Township Number: T 27 S	Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city? 4404 OTT WICHITA KANS					
2 WATER WELL OWNER: RR#, St. Address, Box #: GERALD HARMON City, State, ZIP Code: 4404 OTT WICHITA KS. 67212					
Board of Agriculture, Division of Water Resources Application Number: NONE					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: 1300 Depth(s) Groundwater Encountered 1. 17 ft. 2. 17 ft. 3. 17 ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 12-16-81 Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield 75 gpm Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 9 in. to 12 ft. and 6 in. to 34 ft. WELL WATER TO BE USED AS: 5 Public water supply ☒ 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes ☒ No ☐			
5 TYPE OF BLANK CASING USED: 1 Steel ☒ 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: ☒ Glued ☐ Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ Blank casing diameter 5 in. to 12 in. Dia. 1.59 lbs./ft. Wall thickness or gauge No. 209 Casing height above land surface 12 in. weight 1.59 lbs./ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass ☒ 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped ☒ 7 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20 ft. to 34 ft. From 20 ft. to 34 ft. GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. 6 GROUT MATERIAL: 1 Neat cement 2 ☒ Cement grout 3 Bentonite 4 Other Grout Intervals: From 2 ft. to 12 ft. From 2 ft. to 12 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 ☒ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? WEST How many feet? 30					
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	6	SANDY SOIL MED.-TAN			
6	14	SAND FINE - TAN			
14	22	SAND MED TAN			
22	34	SAND COARSE TAN			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-16-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 12-27-81 under the business name of BEARDEN Pump & Well by (signature) OTW Bearden					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E

SEC.

11

SE 1/4 SW 1/4 NE 1/4

52