

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

27 1 W 1 S 6 E
T R EW sec 1 1/4 1/4 No.

Kansas State Dept. Of Health
(Water Well Contractors)
Forbes-Bldg. 740
Topeka, Kansas 66620

1 Location of well:	County	Township name	Section number	Town number	Range number		
JEDGWICK	DELAND	SW 1/4 NE 1/4	4	T27S	R1W		
Distance and direction from nearest town or city: IN WICHITA KS.			3 Owner of well: DALE J. MURLEY				
Street address of well location if in city: 1632 NEVADA COURT			Address: 1632 NEVADA CT. WICHITA KS				
Locate with "X" in section below: N W E S 1 Mile		Sketch map: DRILLED 8" HOLE TO 10' INSTALLED 4" CASING + GROUTED		4 Well depth: 34 ft. Date of completion: 9-19-75 Well diameter: 8 in.			
2 Type and color of material		From		To		5 ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary	
						6 Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Commercial ☐ Test well ☐	
FILL SAND		0		1		7 Casing: Material: RWP Height: above/below BASEMENT FLOOR - BASEMENT 6' DEEP Threaded ☐ Welded ☒ Surface 12 in. Diam. 30L Weight 455 lbs./ft. 4 in. to 14 ft. depth Drive shoe? ☐ Yes ☒ No	
CLAY & SAND - BROWN		1		3		8 Screen: Manufacturer: CLAYTON MARK Type: BRASS Dia. 1.25 Slot/size: 0.60 Length: 4 FT. Set between 30 ft. and 34 ft. Fittings: GALV IRON PIPE + COUPLINGS Gravel pack ☐ Yes ☒ No Size range of material: _____	
CLAY BROWN		3		5		9 Static water level: BASEMENT FLOOR 105 ft. below land surface Date: 9-19-75	
BROWN SAND - FINE - BROWN		5		6		10 Pumping level below land surfaces: ____ ft. after ____ hrs. pumping ____ g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield: 40 g.p.m.	
MEDIUM SAND - TAN COLOR		6		9		11 Water sample submitted: ☐ Yes ☒ No Date: _____	
MEDIUM SAND RED-BROWN		9		10		12 Well head completion: 12" BASEMENT FLOOR ☐ Pitless adapter ☒ Inches above grade	
DROVE 1.25 GALV PIPE WITH POINT TO				34		13 Well grouted? ☒ Yes ☐ No ☒ Neat cement ☐ Bentonite ☐ Depth: From 0 ft. to 10 ft.	
						14 Nearest source of possible contamination: ft. 10'3" Direction S.W. Type WATER TIGHT SEWER Well disinfected upon completion? ☒ Yes ☐ No	
						15 Pump: Not installed Manufacturer's name: MCDONALD Model number: NA HP 150 Volts 220 Length of drop pipe: 34 ft. capacity 12 g.m.p. Type: ☐ Submersible ☐ Turbine ☒ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
16 Remarks: elevation 1300 FT.						17 Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEV PUMP & WELL Business name: 3142 MENTOR - WICHITA KS License No. 104 Address: 3142 MENTOR - WICHITA KS Signed: [Signature] Date: 10/15/75 Authorized representative	

Forward the white, blue and pink copies to the Kansas State Dept. Of Health.

Form WWC-5