

1 LOCATION OF WATER WELL:		Fraction SE 1/4 NE 1/4 NE 1/4	Section Number 11	Township Number T 27 S	Range Number R 1 E																																				
County: Sedgwick																																									
Distance and direction from nearest town or city street address of well if located within city? 2011 N. West MW-1																																									
2 WATER WELL OWNER: Fina Oil & Chemical Co.																																									
RR#, St. Address, Box #: Box 2159																																									
City, State, ZIP Code: Dallas, TX 75221																																									
Board of Agriculture, Division of Water Resources																																									
Application Number:																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 9-99.40'																																							
		Depth(s) Groundwater Encountered 1. 20' ft. 2. . ft. 3. . ft.																																							
		WELL'S STATIC WATER LEVEL 19.71 ft. below land surface measured on mo/day/yr 1/21/89																																							
		Pump test data: Well water was . ft. after . hours pumping . gpm																																							
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm																																							
		Bore Hole Diameter . in. to . ft., and . in. to . ft.																																							
		WELL WATER TO BE USED AS:																																							
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well																																							
		Was a chemical/bacteriological sample submitted to Department? Yes . No ☒ ; If yes, mo/day/yr sample was submitted																																							
		Water Well Disinfected? Yes . No																																							
5 TYPE OF BLANK CASING USED:																																									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped . ☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . Blank casing diameter 4 in. to 15 ft., Dia . in. to . ft., Dia . in. to . ft. Casing height above land surface . in., weight . lbs./ft. Wall thickness or gauge No. . TYPE OF SCREEN OR PERFORATION MATERIAL: ☒ PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) . 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) . SCREEN-PERFORATED INTERVALS: From 15 ft. to 25 ft., From . ft. to . ft. From . ft. to . ft., From . ft. to . ft. GRAVEL PACK INTERVALS: From 11 ft. to 25 ft., From . ft. to . ft. From . ft. to . ft., From . ft. to . ft.																																									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ Bentonite 4 Other .																																									
Grout Intervals: From 0 ft. to 11 ft., From . ft. to . ft., From . ft. to . ft.																																									
What is the nearest source of possible contamination:																																									
1 Septic tank 4 Lateral lines 7 Pit privy ☒ Fuel storage 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)																																									
Direction from well? East How many feet? 45'																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>6'</td> <td>Dark brn, silty clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6</td> <td>12'</td> <td>Dark brn, sandy clay</td> <td></td> <td></td> <td></td> </tr> <tr> <td>12</td> <td>25'</td> <td>Sand</td> <td></td> <td></td> <td></td> </tr> <tr> <td colspan="6">Grout variance and casing height variance for first mount covers granted 2-21-89 By Darrel Plummer.</td> </tr> <tr> <td colspan="6">Installed watertight locking caps</td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	6'	Dark brn, silty clay				6	12'	Dark brn, sandy clay				12	25'	Sand				Grout variance and casing height variance for first mount covers granted 2-21-89 By Darrel Plummer.						Installed watertight locking caps					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																				
0	6'	Dark brn, silty clay																																							
6	12'	Dark brn, sandy clay																																							
12	25'	Sand																																							
Grout variance and casing height variance for first mount covers granted 2-21-89 By Darrel Plummer.																																									
Installed watertight locking caps																																									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/21/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 496 This Water Well Record was completed on (mo/day/yr) 2-16-89 under the business name of Groundwater Technology by (signature) David James																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.																																									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4