

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u> <u>SE</u>		<u>SE 1/4 NE 1/4 NE 1/4</u>	<u>11</u>	T <u>27</u> S	R <u>1</u> EW <u>(1)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2011 N. West St Wichita KS</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>27'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>19</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>19</u> ft. below land surface measured on mo/day/yr <u>3-22-89</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>12</u> in. to <u>30</u> in. and in. to in.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>			
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ;		If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes No <u>X</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
<u>2 PVC</u>		4 ABS		6 Asbestos-Cement	
Blank casing diameter <u>4</u> in. to <u>12</u> ft. Dia		7 Fiberglass		9 Other (specify below)	
Casing height above land surface <u>2</u> in., weight				CASING JOINTS: Glued Clamped Welded Threaded <u>X</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		3 Stainless steel		5 Fiberglass	
2 Brass		4 Galvanized steel		6 Concrete tile	
SCREEN OR PERFORATION OPENINGS ARE:		8 RMP (SR)			
1 Continuous slot		3 Mill slot		9 ABS	
2 Louvered shutter		4 Key punched		10 Asbestos-cement	
SCREEN-PERFORATED INTERVALS:		11 Other (specify)			
From <u>12</u> ft. to <u>27</u> ft.		12 None used (open hole)			
GRAVEL PACK INTERVALS:		5 Gauzed wrapped			
From <u>10</u> ft. to <u>27</u> ft.		8 Saw cut			
		11 None (open hole)			
		6 Wire wrapped			
		9 Drilled holes			
		7 Torch cut			
		10 Other (specify)			
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
Grout Intervals: From <u>surface</u> ft. to <u>10</u> ft.		4 Other			
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
Direction from well? <u>North</u>		11 Fuel storage			
		12 Fertilizer storage			
		13 Insecticide storage			
		14 Abandoned water well			
		15 Oil well/Gas well			
		16 Other (specify below)			
		How many feet? <u>20</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12	Brown silty CLAY			
12	14	Brown silty fine SAND			
14	30	Brown red to coarse SAND w/gravel			
Grout variance and casing height variance for flush mount covers granted					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>3-22-89</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>496</u> This Water Well Record was completed on (mo/day/yr) <u>3-30-89</u> under the business name of <u>Crowdus Fuel Inc</u> by (signature) <u>Paul Davis</u>					