


1 LOCATION OF WATER WELL: County: Sedgwick SE Fraction SE 1/4 NE 1/4 NE 1/4 Section Number 11 Township Number T 27 S Range Number R 1 EW 6
 Distance and direction from nearest town or city street address of well if located within city? 2011 N West St. Wichita KS MW-6

2 WATER WELL OWNER: Fina Oil & Chemical
 RR#, St. Address, Box #: Box 2159 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Dallas Texas 75221 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 17.5 ft.
 Depth(s) Groundwater Encountered 1. 17.5 ft. 2. 17.20 ft. 3. 9/27/89 ft.
 WELL'S STATIC WATER LEVEL 17.20 ft. below land surface measured on mo/day/yr 9/27/89
 Pump test data: Well water was 6 3/4 ft. after 25 hours pumping 27 gpm
 Est. Yield 27 gpm; Well water was 25 ft. after 27 hours pumping 27 gpm
 Bore Hole Diameter 6 3/4 in. to 25 ft., and 27 in. to 27 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
3 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 Blank casing diameter 2 in. to 12 ft., Dia 12 in. to 40 ft., Dia 40 in. to 40 ft.
 Casing height above land surface 0 in., weight 40 lbs./ft. Wall thickness or gauge No. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 12 None used (open hole)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 12
 SCREEN-PERFORATED INTERVALS: From 12 ft. to 25 ft., From 12 ft. to 25 ft.
 From 0 ft. to 8 ft., From 0 ft. to 8 ft.
 GRAVEL PACK INTERVALS: From 0 ft. to 8 ft., From 0 ft. to 8 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 50
 Grout Intervals: From 0 ft. to 8 ft., From 0 ft. to 8 ft., From 0 ft. to 8 ft., From 0 ft. to 8 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? Northwest How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>3</u>	<u>Sand</u>			
<u>3</u>	<u>12</u>	<u>CLAY</u>			
<u>12</u>	<u>27</u>	<u>Sand</u>			
		<u>Casing and grout variance granted.</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-15-89 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 517 This Water Well Record was completed on (mo/day/yr) 9-28-89
 under the business name of Groundwater Technology Inc. by (signature) Baughman