

NW NE NE SE

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NE 1/4 NE 1/4	Section Number 11	Township Number T 27 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 1737 N. Colorado Wichita, Kansas					
2 WATER WELL OWNER: Travis, Duane RR#, St. Address, Box # #9 Minton Lane City, State, ZIP Code Bella Vista, Arkansas 72714			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 30 ft. ELEVATION: PLUGGED Depth(s) Groundwater Encountered 1. 18 ft. 2. 30 ft. 3. 10-11-91 ft. WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 10-11-91 Pump test data: Well water was 11 ft. after 30 hours pumping 11 gpm Est. Yield 11 gpm: Well water was 30 ft. after 30 hours pumping 11 gpm Bore Hole Diameter 11 in. to 30 in. and 30 in. to 30 in. ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted X Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 1 1/2 in. to 60 ft., Dia 60 in. to 60 in. ft., Dia 60 in. to 60 in. ft. Casing height above land surface 60 in., weight 60 lbs./ft. Wall thickness or gauge No. 60		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) X 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 0 ft. to 6 ft., From 6 ft. to 20 ft., From 20 ft. to 30 ft.		GRAVEL PACK INTERVALS: From 0 ft. to 6 ft., From 6 ft. to 20 ft., From 20 ft. to 30 ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 20 ft., From 20 ft. to 30 ft. Grout intervals: From 0 ft. to 6 ft., From 6 ft. to 20 ft., From 20 ft. to 30 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? East How many feet? 5 ft.					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
		0	6	cement grout	
		6	20	bentonite hole plug	
		20	30	chlorinated sand and gravel	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-11-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 1-27-92 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.