


1 LOCATION OF WATER WELL: County: Sedgewick		Fraction: SE 1/4 SW 1/4 NW 1/4	Section Number: 12	Township Number: T 27 S	Range Number: R 1 E
Distance and direction from nearest town or city street address of well if located within city? 1825 North Kessler					
2 WATER WELL OWNER: Mr. D. H. McMillian RR#, St. Address, Box #: 1825 North Kessler City, State, ZIP Code: Wichita, Kansas 67203			Board of Agriculture, Division of Water Resources Application Number: N/A		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: Depth(s) Groundwater Encountered: 23 ft. 2. 24 ft. 3. 5-24-85 ft. WELL'S STATIC WATER LEVEL: 23 ft. below land surface measured on mo/day/yr Pump test data: Well water was 24 ft. after 1 hours pumping 18 gpm Est. Yield: 60 gpm Well water was 23 ft. after 1 hours pumping 18 gpm Bore Hole Diameter: 11 in. to 23 ft., and 23 in. to 23 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No X			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SRI) 2 PVC 4 ABS Blank casing diameter 6 in. to 35 ft., Dia. 35 in. to 35 ft., Dia. 35 in. to 35 ft. Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 12		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SRI) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 11 SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 6 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) 10		SCREEN-PERFORATED INTERVALS: From 35 ft. to 40 ft., From 40 ft. to 40 ft., From 40 ft. to 40 ft. GRAVEL PACK INTERVALS: From N/A ft. to N/A ft., From N/A ft. to N/A ft., From N/A ft. to N/A ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 6 ft., From 6 ft. to 22 ft., From 22 ft. to 40 ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? North How many feet? 11'			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0	6	Dark Brown Sand/Clay loam			
6	22	light Brown Sand/Clay loam			
22	40	light Brown Medium Coarse Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/24/85 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 285 This Water Well Record was completed on (mo/day/yr) 5/28/85 under the business name of Protheroe Pump & Well Service by (signature) Elmer Protheroe		INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.			

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4