

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

HOUSEHOLD HEAT PUMP RETURN WELL

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

- SEE ATTACHED LETTER -

1. Location of well:		County SEDEWICK	Fraction NW 1/4 SW 1/4 NE 1/4	Section number 12	Township number T 27 S	Range number R 1 W E/W
2. Distance and direction from nearest town or city: MT. CARMEL 1976 N. Street address of well location if in city: WICHITA, KS.		3. Owner of well: JOHN A KRUPP R.R. or street: 1976 N MT. CARMEL City, state, zip code: WICHITA, KS. 67203				
4. Locate with "X" in section below: Sketch map: BORED 9" HOLE TO 13 FT. THEN 6" TO 19 FT. USED SAND BUCKET TO COMPLETE AT 32 FT.		6. Bore hole dia. 9 in. Completion date 8-26-78 Well depth 32 ft. GRADE				
5. Type and color of material		From	To	7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☒ Jetted ☒ Bored ☐ Reverse rotary		
TOP SOIL BLACK		0	3	8. Use: ☐ Domestic ☐ Public supply ☐ Industry ☒ HEAT PUMP RETURN ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
CLAY GRAY		3	7	9. Casing: Material RMP Height Above or below Threads 3/4 Weld WELD Surface 1 in. RMP ☒ PVC ☐ Weight 135 lbs./ft. Dia. 5 in. to 32 ft. depth Wall Thickness: inches 0.200 Dia. 5 in. to 32 ft. depth gage No. 0.200		
CLAY BROWN		11	12	10. Screen: Manufacturer's name SAN FLOWER PLASTICS Type RMP Dia. 5 INCH Slot/gauze 0.031 Length 9 FT. Set between 23 ft. and 32 ft. ft. and ft. Gravel pack? NO Size range of material		
SAND TAN COARSE		12	16	11. Static water level: 19 ft. below land surface Date 8-26-78 mo./day/yr.		
SAND COARSE BROWN		16	19	12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping NA g.p.m. Estimated maximum 35 g.p.m.		
SAND COARSE TAN		19	21	13. Water sample submitted: NO mo./day/yr.		
SAND COARSE BROWN		21	32	14. Well head completion: 12 CASING EXTENDS ☒ Pitless adapter 12 inches above grade		
				15. Well grouted? YES With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From 2.5 ft. to 13 ft.		
				16. Nearest source of possible contamination: PLASTIC SEWER ft. 35 Direction EAST Type SEWER Well disinfected upon completion? ☐ Yes ☒ No		
				17. Pump: ☒ Not installed Manufacturer's name Model number 20 HP 1 Volts 115 Length of drop pipe 20 ft. capacity 1 g.p.m. Type: INJECTING ☐ Submersible ☐ Turbine ☐ Reciprocating ☐ Jet ☐ Other		
18. Elevation: 1300 Topography: ☐ Hill ☐ Slope ☒ Upland ☒ Valley		19. Remarks: THIS RETURN WELL IS CONSTRUCTED TO SAME SPECS. AS THE SUPPLY WELL 25' WEST.		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP WELL 104 Business name 3100 MENTOR License No. WICHITA Address 101 W. Beaver Signed Joe W. Bearden Date 10-1-78 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5