


1 LOCATION OF WATER WELL: County: SEDGWICK Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 13 Township Number T 27 S Range Number R 1 E		Distance and direction from nearest town or city street address of well if located within city? 3935 WEST 18TH ST. WICLIATA, KS			
2 WATER WELL OWNER: AMOCO OIL COMPANY RR#, St. Address, Box #: 8700 INDIAN CREEK PKWAY City, State, ZIP Code: OVERLAND PARK, KS 66210		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 24.5 ft. ELEVATION: Depth(s) Groundwater Encountered: 99% dry ft. 2. NA ft. 3. NA ft. WELL'S STATIC WATER LEVEL: 99% dry ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield: NA gpm; Well water was 25' ft. after hours pumping gpm Bore Hole Diameter: 6 1/4 in. to 25' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Blank casing diameter: 2 1/2 in. to 15 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 40 in., weight lbs./ft. Wall thickness or gauge No. 40		CASING JOINTS: Glued Clamped Welded Threaded.			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 1/4" Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 12 None used (open hole) 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS: From 15' ft. to 25' ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 13 ft. to 25 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 13 ft. to 11 ft. From 11 ft. to 4 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 FUEL TANKS 13 Insecticide storage Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	6"	ASPHALT			
6"	3'	SANDY CLAY, MED			
3'	18'	SANDY, FINE			
18'	25'	SANDY, COARSE, WET			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-9-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 519 This Water Well Record was completed on (mo/day/yr) 4-9-91 under the business name of West Hazmat Drilling Corp by (signature) Harry V. Sanders					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					