

1 LOCATION OF WATER WELL:		Fraction SW	Section Number 13	Township Number T 27 S	Range Number R 1 E
County: Sedgwick		NE 1/4	NE 1/4		
Distance and direction from nearest town or city street address of well if located within city? 2920 W 18th					

2 WATER WELL OWNER: moore, Ronald D		Board of Agriculture, Division of Water Resources Application Number: NA
RR#, St. Address, Box #: 2920 W 18th		
City, State, ZIP Code: Wichita KS 67203		

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: 18 ft.	
		Depth(s) Groundwater Encountered 1 ft. 18 ft. 3. ft.	
		WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 8-10-83	
		Pump test data: Well water was 21 ft. after 1 hours pumping 20 gpm	
		Est. Yield 70 gpm: Well water was 10 ft. after 6 hours pumping 34 gpm	
		Bore Hole Diameter 9 in. to 10 ft., and 6 in. to 34 ft.	
WELL WATER TO BE USED AS:		5 Public water supply ☒ 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ ; If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes ☒ No ☒			

5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒	
1 Steel ☒ 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded ☒	
2 PVC 4 ABS		7 Fiberglass Threaded ☒	
Blank casing diameter 6 in. to 29 ft., Dia 12 in. to 200 lbs./ft. Wall thickness or gauge No. 200			
Casing height above land surface 12 in., weight 29 lbs./ft.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement	
1 Steel 3 Stainless steel 5 Fiberglass ☒ 8 RMP (SR) 11 Other (specify) ☒		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped ☒ 8 Saw cut 11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ☒	
SCREEN-PERFORATED INTERVALS:		From 29 ft. to 34 ft. From 29 ft. to 34 ft.	
GRAVEL PACK INTERVALS:		From 29 ft. to 34 ft. From 29 ft. to 34 ft.	

6 GROUT MATERIAL:		1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other	
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 25 ft.			
What is the nearest source of possible contamination:			
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well		11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)		13 Insecticide storage	
☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard			
Direction from well? EAST		How many feet? 25 feet	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Tan fine fill sand			
3	8	LT Brn sand/clay loam			
8	15	Brk. Brn clay			
15	34	LT Brn. med coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-10-83 and this record is true to the best of my knowledge and belief. Kansas	
Water Well Contractor's License No. 295 This Water Well Record was completed on (mo/day/yr) 8-12-83	
under the business name of Protheroe Pump & Well Service by (signature) Alvin Protheroe	

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

27 R

1

E

SEC.

13

NE 1/4

SW 1/4

NE 1/4