


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
		SEDGWICK	NE NW NE	14	T 27 S R 1W	E/W
2. Distance and direction from nearest town or city:		3. Owner of well:				
Street address of well location if in city:		F.M. DEVELOPEMENT				
1227 N. CLARA WICHITA KS.		AR. or street: 1630 LYNN HURST WICHITA KS 67211				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 4-22-78		
		BORED 8" HOLE TO 10 FT. INSTALLED 4" CASING - DROVE PIPE + POINT TO COMPLETION GROUTED CASING		Well depth 24 ft.		
5. Type and color of material		From	To	7. Cable tool Rotary ☒ Driven ☒ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary		
SAND BROWN MED		0	2	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
SAND COARSE TAN		2	6	9. Casing: Material RMP Height: 12 in. below or below		
CLAY SANDY GRAY		6	7	Threading: 204 X Surface 12 in.		
SAND BROWN MED.		7	10	RMP: X PVC Weight 1.55 lbs./ft.		
DROVE 1.25" SAND		10		Dia. 4 in. to 11 ft. depth Wall thickness: inches or		
POINT + GALV. PIPE TO			24	Dia. in. to ft. depth gage No. 100		
				10. Screen: Manufacturer's name CLAYTON		
				Type BRASS Dia. 1.25		
				Slot/gauze .060 Length 4 ft.		
				Set between 20 ft. and 24 ft.		
				Gravel pack? NO Size range of material		
				11. Static water level: 11 ft. below land surface 4-22-78		
				12. Pumping level below land surfaces: NA g.p.m.		
				Estimated maximum yield 35 g.p.m.		
				13. Water sample submitted: No Date		
				14. Well head completion: 12 BASEMENT		
				Pitless adapter 12 Inches above grade		
				15. Well grouted? YES		
				With: Neat cement Bentonite Concrete		
				Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: PLASTIC		
				ft. 10 Direction SW Type 3 INCH		
				Well disinfected upon completion? X Yes No		
				17. Pump: Nat. installed		
				Manufacturer's name FFW		
				Model number 50 HP 50 Volts 110		
				Length of drop pipe 24 ft. capacity 12 g.p.m.		
				Type: Submersible Turbine		
				Jet Reciprocating		
				Centrifugal Other		
18. Elevation: 1300 FT.		19. Remarks:		20. Water well contractor's certification:		
Topography: Hill Slope Upland Valley				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
				BEARDEN PUMPWELL 1104		
				Business name 3142 MENTON License No. WICHITA		
				Address 105 W. Beach Date 5/10/78		
				Signed D. W. Beard Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5