

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well: <u>Sedg.</u>		Fraction: <u>NE 1/4 NE 1/4 NW 1/4</u>		Section number: <u>14</u>		Township number: <u>27</u> S <u>1</u> E		Range number: <u>1</u> W	
2. Distance and direction from nearest town or city: Street address of well location if in city: <u>4514 Whitehall W. Chita</u>				3. Owner of well: <u>Ken Farms</u> R.R. or street: <u>4514 Whitehall</u> City, state, zip code: <u>Whitehall KS 67203</u>					
4. Locate with "X" in section below:				Sketch map:		6. Bore hole dia. <u>4 1/2</u> in. Completion date: <u>10/1/77</u> Well depth <u>46</u> ft.			
						7. ☒ Cable tool ☒ Rotary ☐ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary			
5. Type and color of material				From		To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other	
Top Soil				0		6		9. Casing: Material <u>PVC</u> Height Above or below Threaded ☐ Welded ☒ Surface <u>12</u> in. RMP ☐ PVC ☒ Weight <u>237</u> lbs./ft. Dia. <u>5</u> in. to <u>4 1/2</u> ft. depth Wall Thickness: inches <u>1/4</u> Dia. <u>5</u> in. to <u>4 1/2</u> ft. depth gage No. <u>214</u>	
brown clay				6		18		10. Screen: Manufacturer's name <u>MPI</u> Type <u>PVC</u> Dia. <u>5 1/2</u> in. Slot/duze <u>1/16</u> Length <u>5 1/2</u> ft. Set between <u>11</u> ft. and <u>46</u> ft. <u>46</u> ft. and <u>46</u> ft. Gravel pack? ☒ Size range of material <u>3/8</u>	
fine to medium sand				18		31		11. Static water level: <u>13</u> ft. below land surface Date <u>10/1/77</u>	
clay				31		32		12. Pumping level below land surfaces: <u>14</u> ft. after <u>1/2</u> hrs. pumping <u>18</u> g.p.m. <u>14</u> ft. after <u>1</u> hrs. pumping <u>18</u> g.p.m. Estimated maximum yield <u>50</u> g.p.m.	
med. to coarse gravel				32		46		13. Water sample submitted: <u>13</u> mo./day/yr. Yes ☒ No ☐ Date <u>10/1/77</u>	
								14. Well head completion: ☒ Pitless adapter <u>12</u> inches above grade	
								15. Well grouted? <u>yes</u> With: ☒ Neat cement ☐ Bentonite ☐ Concrete Depth: From <u>3</u> ft. to <u>13</u> ft.	
								16. Nearest source of possible contamination: ft. <u>10</u> Direction <u>North</u> type <u>well</u> Well disinfected upon completion? ☒ Yes ☐ No	
								17. Pump: ☒ Submersible ☐ Turbine Manufacturer's name <u>Valley</u> Not installed Model number <u>1802</u> HP <u>3/4</u> Volts <u>220</u> Length of drop pipe <u>25</u> ft. capacity <u>1/8</u> g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other	
18. Elevation:		19. Remarks: <u>Contractor to furnish 4x4x4 reinforced slab around well at grade</u> <u>(Stauffer Real/Tores Contractors)</u>							
Topography: ☐ Hill ☐ Slope ☒ Upland ☐ Valley		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <u>Weninger Drilling</u> 318 Business name <u>Kolovich</u> License No. <u>14</u> Address <u>14</u> Signed <u>10/1/77</u> Date <u>10/1/77</u> Authorized representative							

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5