

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
FROG WICK		NE 1/4 NW NE	14	27	S R 1W	E/W
2. Distance and direction from nearest town or city:		3. Owner of well:				
1239 N CLARA		FM DEVELOPEMENT				
Street address of well location if in city:		R.R. or street:				
WICHITA KANS		1630 LYNN HURST				
4. Locate with "X" in section below:		City, state, zip code:				
WICHITA KANS 67211		6. Bore hole dia. 8 in. Completion date 5/22/78				
Sketch map: BORED 8" HOLE TO 10FT. INSTALLED 4" CASING - DROVE PIPE + POINT TO COMPLETION - GROUTED CASING		Well depth 24 ft.				
5. Type and color of material		7. Cable tool Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary ☐				
From To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ ☐ Lawn ☐ Oil field water ☐ Other ☐				
SAND BROWN MED 0 2		9. Casing: Material RMP Height Above or below BASEMENT				
SAND COARSE TAN 2 6		Threading 24 Welded ☒ Surface 12 in.				
CLAY SANDY GRAY 6 8		RMP ☒ PVC ☐ Weight 155 lbs./ft.				
SAND BROWN COARSE 8 10		Dia. 4 in. to 11 ft. depth Wall Thickness: inches or				
DROVE 1.25" SAND POINT 10		Dia. 1 in. to ft. depth gage No. 200				
20' GALV. PIPE TO 24		10. Screen: Manufacturer's name CLAYTON				
		Type BRASS Dia. 1.25 in.				
		Slot/gauze .060 Length 4 ft.				
		Set between 20 ft. and 44 ft.				
		Gravel pack? NO Size range of material				
		11. Static water level 11 ft. below land surface Date 5/22/78				
		12. Pumping level below land surfaces:				
		ft. after hrs. pumping NA g.p.m.				
		ft. after hrs. pumping NA g.p.m.				
		Estimated maximum yield 35 g.p.m.				
		13. Water sample submitted: mo./day/yr.				
		Yes ☒ No ☐ Date				
		14. Well head completion:				
		Pitless adapter 12 Inches above grade				
		15. Well grouted? YES				
		With: ☒ Neot cement ☐ Bentonite ☐ Concrete				
		Depth: From 0 ft. to 10 ft.				
		16. Nearest source of possible contamination:				
		ft. 11 Direction 30 Type PLASTIC				
		Well disinfected upon completion? ☒ Yes ☐ No				
		17. Pump: Not installed				
		Manufacturer's name F&W				
		Model number GPJ053 HP 1.50 Volts 115				
		Length of drop pipe 24 ft. capacity 12 g.p.m.				
		Type:				
		☒ Submersible ☐ Turbine ☐ Reciprocating ☐ Other				
		☒ Jet ☐ Centrifugal				
18. Elevation: 1300		20. Water well contractor's certification:				
Topography: Hill ☐ Slope ☐ Upland ☐ Valley ☒		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
19. Remarks:		Signed: BEARDEN Pump & Well				
		Business name 3144 MENTOR License No. WICHITA				
		Address 6/24/78				
		Authorized representative				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5