


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
SEDGWICK		NE NW NE	14	T 27 S R 1W E/W		
2. Distance and direction from nearest town or city:			3. Owner of well:			
Street address of well location if in city: 1202 N. DORIS WICHITA KANS			F M DEVELOPEMENT 1630 LYNNHURST WICHITA KS 67211			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 8-21-78		
		BORED, 8" HOLE TO 10' INSTALLED 4" CASING DROVE PIPE & POINT TO COMPLETION GRUNTED CASING		Well depth 24' BASEMENT		
5. Type and color of material				From	To	7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary
SAND BROWN COARSE				0	3	8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other
SAND MEDIUM TAN				3	6	9. Casing: Material RMP Height: Above or below Threading SOL Welded X Surface 12 in. RMP PVC Weight 1.55 lbs./ft. Dia. 4 in. to 11 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 200
SANDY CLAY GRAY				6	8	10. Screen: Manufacturer's name CLAYTON Type BRASS Dia. 1.25" Slot/size 0.60 Length 4 FT. Set between 90 ft. and 24 ft. Gravel pack? NO Size range of material
SAND BROWN MEDIUM				8	10	11. Static water level: 11 ft. below land surface Date 8-21-78
DROVE 1.25" CALK.				10		12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 35 g.p.m.
PIPE & SAND POINT TO				24		13. Water sample submitted: Yes No Date
						14. Well head completion: Pitless adapter 12 inches above grade
						15. Well grouted? YES With: Neat cement Bentonite Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: PLASTIC ft. 10 Direction EAST Type SEWER Well disinfected upon completion? Yes No
						17. Pump: Not installed Manufacturer's name FFW Model number CR1055 HP 50 Volts 115 Length of drop pipe 24 ft. capacity 12 g.p.m. Type: Submersible Turbine Jet Reciprocating Centrifugal Other
						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN RUMPTWELL Business name License No. Address 3142 MENTOR WICHITA KS Signed [Signature] Date 8/29/78
18. Elevation: 1300'		19. Remarks:				
Topography: Hill Slope Upland Valley						

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5