


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
SEDGWICK		NE 1/4 NW 1/4 NE 1/4	14	27	S R 1W	E/W
2. Distance and direction from nearest town or city:		3. Owner of well:				
IN WICHITA		JIM BENDER (PARK MID CONSTRUCTION)				
Street address of well location if in city:		R.R. or street:				
4602 WHITE HALL		322 LAURA 67211				
WICHITA KANS		City, state, zip code: WICHITA KANS				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 9-8-76		
		DRILLE 8" HOLE TO 10' INSTALLED 4" CASING + GROUTED		Well depth 25 ft. FROM 6' BASEMENT		
5. Type and color of material		From	To	7. Cable tool Rotary ☒ Driven ☒ Dug ☐ Hollow rod ☐ Jetted ☒ Reversed ☐ Reverse rotary ☐		
SANDY - MEDIUM TAN		0	1.5	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
SAND MEDIUM TAN		1.5	4	9. Casing: Material RMP Height: Above or below		
SAND FINE TAN		4	8	Threaded ☐ Welded ☒ Surface ☒ BASEMENT FLOOR		
GRAVEL MEDIUM REDDISH		8	10	RMP ☒ PVC ☐ Weight 155 lbs./ft.		
1/2 - DROVE 1.25 PIPE + SAN		10		Dia. 4 in. to 11 ft. depth Wall Thickness: inches or		
POINT TO			25	Dia. in. to ft. depth gage No. 200		
				10. Screen: Manufacturer's name CLAYTON		
				Type BRASS Dia. 1.25"		
				Slot/gauze 2-060 Length 4 ft.		
				Set between 21 ft. and 25 ft.		
				Gravel pack? NO Size range of material		
				11. Static water level: BASEMENT FLOOR mo./day/yr.		
				10 ft. below land surface Date 9-8-76		
				12. Pumping level below land surfaces:		
				ft. after hrs. pumping NA g.p.m.		
				ft. after hrs. pumping 40 g.p.m.		
				Estimated maximum yield 40 g.p.m.		
				13. Water sample submitted: mo./day/yr.		
				Yes ☒ No ☐ Date		
				14. Well head completion: BASEMENT FLOOR		
				Pitless adapter 11 inches above grade		
				15. Well grouted? YES		
				With: ☒ Neat cement ☐ Bentonite ☐ Concrete		
				Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination:		
				ft. 12 Direction SE Type PLASTIC		
				Well disinfected upon completion? ☒ Yes ☐ No		
				17. Pump: Not installed		
				Manufacturer's name BFW		
				Model number SCOTIS HP 150 Volts 115		
				Length of drop pipe 25 ft. capacity 14 g.p.m.		
				Type:		
				☒ Submersible ☐ Turbine		
				☒ Jet ☐ Reciprocating		
				☐ Centrifugal ☐ Other		
18. Elevation: 1300 FT.		19. Remarks:		20. Water well contractor's certification:		
Topography:				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
☒ Hill				BEARDEN PUMP & WELL INC.		
☐ Slope				Business name		
☐ Upland				Address 3122 MENTOR WICHITA KANS		
☒ Valley				Signed O.W. Bearden Date 10-11-76		
				Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5