

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
SEDCWICK		NE 1/4 NW NE	14	T 27 S	R 1 E	W
2. Distance and direction from nearest town or city:		3. Owner of well:		Completion date		
Street address of well location if in city: 1227 SMITH WICHITA KANS		DAVID DUNHAM 1227 SMITH WICHITA KANS, 67211		9-30-79		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Well depth 24 ft. Completion date 9-30-79		
		BORED 8" HOLE TO 10' INSTALLED 4" CASING - DROVE PIPE & POINT TO COMPLETION - GROUTED CASING		7. Cable tool Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary		
5. Type and color of material		From		To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other
SAND COARSE BROWN		0		2		9. Casing: Material RMP Height: Above or below
CLAY GRAY		2		4		Threaded ☒ Welded ☒ Surface 1 1/2 in.
CLAY SANDY GRAY		4		6		RMP ☒ PVC ☐ Weight 1.55 lbs./ft.
SAND MEDIUM GRAY		6		7		Dia. 7 in. to 11 ft. depth Wall Thickness: inches or
SAND TAN MED.		7		10		Dia. in. to ft. depth gage No. 0.100
DROVE POINT & PIPE TO COMPLETION AT				24		10. Screen Manufacturer's name CLAYTON MARK STAINLESS STEEL Type 1/25 Slot/gauze 860 Length 4 FT. Set between 20 ft. and 24 ft. Gravel pack? NO Size range of material
						11. Static water level: 10 ft. below land surface Date 8-30-79
						12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 40 g.p.m.
						13. Water sample submitted: Yes ☒ No ☐ Date
						14. Well head completion: Pitless adapter 12 Inches above grade
						15. Well grouted? YES With: Neat cement ☐ Bentonite ☒ Concrete Depth: From 0 ft. to 10 ft.
						16. Nearest source of possible contamination: ft. Direction 1200 ft. PLASTIC SEWER Well disinfected upon completion? Yes ☒ No ☐
						17. Pump: CUSTOMER'S Not installed Manufacturer's name MYERS Model number NOT KNOWN HP 150 Volts 230 Length of drop pipe 24 ft. capacity 12 g.p.m. Type: Submersible ☒ Turbine ☐ Reciprocating ☐ Centrifugal ☐ Other ☐
18. Elevation: 1300'		19. Remarks:		20. Water well contractor's certification:		
Topography: Hill ☐ Slope ☐ Upland ☐ Valley ☒				This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP & WELL 1044 Business name 3422 MENTOR, WICHITA License No. Address 612 W. Bearden Signed 9/12/79 Date 9/12/79 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5