


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
		SEDGWICK	NE NE SE	15	T 27 S	R 1W E/W
2. Distance and direction from nearest town or city:		3. Owner of well:				
Street address of well location if in city:		R.R. or street:				
5902 FRANKLIN		WOOD CUSTOM HOMES				
WICHITA KS		906 N ARAPAHO				
		WICHITA KANS 67212				
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 8 in. Completion date 5-31-78		
		BORED 8" HOLE TO 6.5 FT. INSTALLED 4" CASING - DROVE PIPE + POINT TO COMPLETE GROUTED CASING.		Well depth 25 ft. FROM BASEMENT		
				Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary ☐		
5. Type and color of material		From		To		8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other
						9. Casing: Material RMP Height Above or below BASEMENT
						Threading SOL Welded ☒ Surface 19 in.
						RMP RMP PVC Weight 7.55 lbs./ft.
						Dia. 4 in. to 7.5 ft. depth Wall Thickness: inches or
						Dia. in. to ft. depth gage No. 0.200
						10. Screen: Manufacturer's name CLAYTON
						Type BRASS Dia. 1.25 INCH
						Slot/gauze 0.060 Length 4 FT.
						Set between 21 ft. and 25 ft.
						Gravel pack? NO Size range of material
SAND COARSE TAN		03				11. Static water level: mo./day/yr.
SAND COARSE RED		36.5				6.5 ft. below land surface Date 5/31/78
SAND COARSE RED H2O		6.5				12. Pumping level below land surfaces:
DROVE PIPE + POINT TO						ft. after hrs. pumping NA g.p.m.
COMPLETION AT		25				ft. after hrs. pumping g.p.m.
						Estimated maximum yield 35 g.p.m.
						13. Water sample submitted: mo./day/yr.
						Yes ☒ No ☐ Date
						14. Well head completion:
						Pitless adapter 12 BASEMENT
						15. Well grouted? YES
						With: ☒ Neat cement ☐ Bentonite ☐ Concrete
						Depth: From 0 ft. to 6.5 ft.
						16. Nearest source of possible contamination:
						ft. 11 Direction WEST Type PLASTIC
						Well disinfected upon completion? ☒ Yes ☐ No
						17. Pump: Not installed
						Manufacturer's name FFW
						Model number CP1055 HP 050 Volts 230
						Length of drop pipe 25 ft. capacity 12 g.p.m.
						Type:
						☒ Submersible ☐ Turbine
						☒ Jet ☐ Reciprocating
						☐ Centrifugal ☐ Other
18. Elevation: 1300 FT.		19. Remarks:		20. Water well contractor's certification:		
Topography:				This well was drilled under my jurisdiction and this report		
☐ Hill				is true to the best of my knowledge and belief.		
☐ Slope				BEAR DEN PUMP & WELL		
☐ Upland				Business name		
☒ Valley				Address 3142 MENTOR WICHITA KS		
				Signed Otis W. Beards Date 7/3/78		
				Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5