

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County: SEDGWICK	Fraction: NE 1/4 NE 1/4 SE 1/4	Section number: 15	Township number: T 27 S	Range number: R 1 W E/W															
2. Distance and direction from nearest town or city: Street address of well location if in city: 5910 FRANKLIN WICHITA KANS				3. Owner of well: WOOD CUSTOM HOMES R.R. or street: 906 N ARAPAH City, state, zip code: WICHITA KANS 67212																	
4. Locate with "X" in section below: Sketch map: BORED 8" HOLE TO 6.5 FT. INSTALLED 4" CASING - DROVE PIPE + POINT TO COMPLETION GROUTED CASING				6. Bore hole dia. 8 in. Completion date: 3/9/79 Well depth: 28 ft. BASEMENT																	
5. Type and color of material				7. ☐ Cable tool ☐ Rotary ☒ Driven ☐ Dug ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary																	
				8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other																	
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>From</th> <th>To</th> </tr> </thead> <tbody> <tr> <td>SAND COARSE TAN</td> <td>0</td> <td>3</td> </tr> <tr> <td>SAND COARSE RED</td> <td>3</td> <td>6.5</td> </tr> <tr> <td>SAND COARSE RED H2O</td> <td>6.5</td> <td></td> </tr> <tr> <td>DROVE PIPE + POINT TO COMPLETION AT</td> <td></td> <td>28</td> </tr> </tbody> </table>					From	To	SAND COARSE TAN	0	3	SAND COARSE RED	3	6.5	SAND COARSE RED H2O	6.5		DROVE PIPE + POINT TO COMPLETION AT		28	9. Casing: Material RMP Height: 3 Above or below Threaded 304 Welded X Surface 12 in. RMP X PVC X Weight 1.55 lbs./ft. Dia. 4 in. to 7.5 depth Wall Thickness: inches or Dia. 1 in. to 7.5 depth gage No. 0.200		
					From	To															
SAND COARSE TAN	0	3																			
SAND COARSE RED	3	6.5																			
SAND COARSE RED H2O	6.5																				
DROVE PIPE + POINT TO COMPLETION AT		28																			
				10. Screen: Manufacturer's name CLAYTON Type BRASS Dia. 1.25 in. Slot/gauze 0.60 Length 4 ft. Set between 24 ft. and 28 ft. 6 ft. and 6 ft. Gravel pack? NO Size range of material																	
				11. Static water level: 6.5 ft. below land surface Date 3/9/79 mo./day/yr.																	
				12. Pumping level below land surfaces: ____ ft. after ____ hrs. pumping NA g.p.m. ____ ft. after ____ hrs. pumping ____ g.p.m. Estimated maximum yield 35 g.p.m.																	
				13. Water sample submitted: ____ mo./day/yr. ☐ Yes ☒ No Date																	
				14. Well head completion: 12 BASEMENT ____ Pitless adapter ____ inches above grade																	
				15. Well grouted? YES With: ____ Neat cement ____ Bentonite X Concrete Depth: From 0 ft. to 6.5 ft.																	
				16. Nearest source of possible contamination: 12 Direction EAST Type SEWER Well disinfected upon completion? ☒ Yes ____ No																	
				17. Pump: PFW Not installed Manufacturer's name PFW Model number CR055 HP 50 Volts 220 Length of drop pipe 28 ft. capacity 12 g.p.m. Type: ☐ Submersible ☐ Turbine ☒ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other																	
18. Elevation: 1300 ft.		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN PUMP WELL Business name 3157 MENTOR WICHITA License No. 104 Address 3157 MENTOR WICHITA Signed OK W Bearden Date 4/12/79 Authorized representative																	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5