


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SW 1/4 SW 1/4 SE 1/4	17	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city?				52895001 4717	
103' NNE of the Intersection of Central Avenue West & Caddy Street, Wichita, KS				Amoco No. 0717	MW-4
2 WATER WELL OWNER: Groundwater Management Section, Amoco Oil Company					
RR#, St. Address, Box #: 7201 E. 38th Street, Space 7253				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code: Tulsa, OK 74145				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 26.5 ft. ELEVATION: Approx. Surface Elev: 1330			
		Depth(s) Groundwater Encountered 1. 20 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 19.9 ft. below land surface measured on mo/day/yr 02/20/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 27 ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 2 in. to 11.5 ft. Dia		7 Fiberglass			
Casing height above land surface -2 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40		8 Air conditioning 11 Injection well			
TYPE OF SCREEN OR PERFORATION MATERIAL:		9 Dewatering 12 Other (Specify below)			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Monitoring well			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
SCREEN OR PERFORATION OPENINGS ARE:		Water Well Disinfected? Yes No X			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 11.5 ft. to 26.5 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 10.5 ft. to 27 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 8.5 ft. From 8.5 ft. to 10.5 ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? NNE How many feet? 15					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5.5	Dark Gray-Brown Lean Silty Clay			
5.5	11.5	Red-Brown Lean Silty Clay			
11.5	17.5	Light Brown Medium Sand			
17.5	27	Light Brown Coarse Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 02/16/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416. This Water Well Record was completed on (mo/day/yr) 3/28/89 under the business name of Terracon Consultants, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					