


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

Billed to: Twenty First Elec.

1. Location of well:	County: <u>Sedgwick</u>	Fraction: <u>1/4 NE 1/4 NW 1/4</u>	Section number: <u>17</u>	Township number: <u>27</u>	Range number: <u>1</u>
2. Distance and direction from nearest town or city:	3. Owner of well: <u>Dan Gates</u>		R.R. or street: <u>1201 North Westlink</u>		
Street address of well location if in city: <u>Wichita, Ks.</u>		City, state, zip code: <u>Wichita Kansas</u>			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. <u>50</u> in. Completion date <u>12-29-77</u>	
				Well depth <u>50</u> ft.	
5. Type and color of material		From	To	7. ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug	
<u>Topsoil</u>		<u>0</u>	<u>3</u>	☐ Hollow rod ☐ Jetted ☐ Bored ☐ Reverse rotary	
<u>Clay</u>		<u>3</u>	<u>12</u>	8. Use: ☐ Domestic ☐ Public supply ☐ Industry	
<u>Fine Sand</u>		<u>12</u>	<u>30</u>	☒ Irrigation ☐ Air conditioning ☐ Stock	
<u>Medium Sand</u>		<u>30</u>	<u>50</u>	☒ Lawn ☐ Oil field water ☐ Other	
				9. Casing: Material <u>styrofoam</u> Height: <u>above</u> or below	
				Threaded ☒ Welded ☐ Surface <u>12</u> in.	
				RMP ☒ PVC ☐ Weight <u>12</u> lbs./ft.	
				Dia. <u>5</u> in. to <u>50</u> ft. depth Wall Thickness: inches or	
				Dia. <u>5</u> in. to <u>50</u> ft. depth gage No. <u>1200</u>	
				10. Screen: Manufacturer's name <u>Sunflower Plastics</u>	
				Type <u>styrofoam</u> Dia. <u>5</u>	
				Gauge gauze <u>06</u> Length <u>15</u> ft.	
				Set between <u>35</u> ft. and <u>50</u> ft.	
				Gravel pack? <u>yes</u> Size range of material <u>1/4-1/8"</u>	
				11. Static water level: <u>30</u> ft. below land surface Date <u>12-29-77</u>	
				12. Pumping level below land surfaces:	
				<u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m.	
				<u> </u> ft. after <u> </u> hrs. pumping <u> </u> g.p.m.	
				Estimated maximum yield <u> </u> g.p.m.	
				13. Water sample submitted: <u> </u> mo./day/yr.	
				☐ Yes ☐ No Date <u> </u>	
				14. Well head completion: <u>12</u> capped	
				<u> </u> Pitless adapter <u>12</u> inches above grade	
				15. Well grouted? <u>yes</u>	
				With: <u> </u> Neat cement ☒ Bentonite ☐ Concrete ☐	
				Depth: From <u>40</u> ft. to <u>14</u> ft.	
				16. Nearest source of possible contamination: <u>City Sewer</u>	
				ft. <u>50</u> Direction <u>W.</u> Type <u> </u>	
				Well disinfected upon completion? ☒ Yes ☐ No	
				17. Pump: ☒ Not installed	
				Manufacturer's name <u> </u>	
				Model number <u> </u> HP <u> </u> Volts <u> </u>	
				Length of drop pipe <u> </u> ft. capacity <u> </u> g.p.m.	
				Type:	
				☐ Submersible ☐ Turbine	
				☐ Jet ☐ Reciprocating	
				☐ Centrifugal ☐ Other	
18. Elevation:		19. Remarks:			
Topography:		<u>Well to be used for sprinkler system.</u>			
☐ Hill					
☒ Slope					
☐ Upland					
☐ Valley					
		20. Water well contractor's certification:			
		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
		Business name <u>Sharp Well Pump</u>			
		Address <u>Wichita, Kans</u>			
		Signed <u>M. Arnold</u> Date <u>1-8-79</u>			
		Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5