


1 LOCATION OF WATER WELL: County: SEDGWICK Fraction SW 1/4 NE 1/4 NE 1/4 Section Number 17 Township Number T 27 S Range Number R 1 E		Distance and direction from nearest town or city street address of well if located within city? 1238 WADDOINGTON - WICHITA KANS					
2 WATER WELL OWNER: RR#, St. Address, Box # : COY MORGAN WICHITA KS. City, State, ZIP Code : 1238 WADDOINGTON 67212		Board of Agriculture, Division of Water Resources Application Number: NONE					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 38 ft. ELEVATION: 1300 Depth(s) Groundwater Encountered 1. 21 ft. 2. BASEMENT ft. 3. 8/15/83 ft. WELL'S STATIC WATER LEVEL 21 ft. below and surface measured on mo/day/yr Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield 60 gpm: Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 9 in. to 10 ft., and 6 in. to 38 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☐ If yes, mo/day/yr sample was submitted					
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☐ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ☐ Blank casing diameter 5 in. to 31 in. Dia. 1.59 in. to 30R 24 in. Dia. 30R 24 in. to 30R 24 in. Dia. Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 30R 24 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 3.0 ft. to 38 ft. From 3.0 ft. to 38 ft. From 3.0 ft. to 38 ft. From 3.0 ft. to 38 ft. GRAVEL PACK INTERVALS: From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft. From NONE ft. to NONE ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft. From 10 ft. to 10 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? EAST How many feet? 12							
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG					
0	2	7	12	SAND - TAN			
2	12	12	22	SANDY RED CLAY			
12	22	22	29	SAND TAN FINE			
22	29	29	38	SAND TAN MED			
29	38	38		SAND TAN COARSE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/15/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 104 This Water Well Record was completed on (mo/day/yr) 9/10/83 under the business name of BEARDEN Pump & Well by (signature) Chris W. Bearden INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blank, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							

OFFICE USE ONLY

T

27

R

E

SEC.

17

SW 1/4

NE 1/4

NE 1/4