

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SE ¼ SE ¼ SE ¼	18	T 27 S	R 1 E/W
Distance and direction from nearest town or city street address of well if located within city?					
½ North of Central, ¼ West of Maize Road Wichita, Kansas					
2 WATER WELL OWNER: Regency Plaza Addition					
RR#, St. Address, Box # : % Sprinkler Ststem Specialist - Don Miller Board of Agriculture, Division of Water Resources					
City, State, ZIP Code : 12110 Dove Hill Dr. Wichita, Ks. Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION:				
Diagram of a section box divided into four quadrants: NW, NE, SW, and SE. An 'X' is marked in the SE quadrant.	Depth(s) Groundwater Encountered 1. 26 ft. 2. ft. 3. ft.				
	WELL'S STATIC WATER LEVEL . . . 26 ft. below land surface measured on mo/day/yr . . . 8-10-84				
	Pump test data: Well water was ft. after hours pumping gpm				
	Est. Yield gpm: Well water was ft. after hours pumping gpm				
	Bore Hole Diameter . . . 1.1 . . . in. to ft., and in. to ft.				
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... <u>X</u> ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 2 PVC 4 ABS ===== Blank casing diameter 5 in. to 7.0 ft., Dia. Cer-Mac Styrene SDR-26 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS ===== SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 70 ft. to 110 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 14 ft. to 110 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? How many feet? None Apparent					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	29	01 Clay			
29	41	07 Fine Sand			
41	57	01 Clay			
57	70	07 Fine Sand			
70	110	08 Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-10-84 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 1-30-85					
under the business name of Harp Well & Pump Service Inc by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					