


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 18	Township Number T 27 S	Range Number R 1 W E/W
Distance and direction from nearest town or city street address of well if located within city? 909 North Maize Road Wichita, Kansas 67212					
2 WATER WELL OWNER: Timber Grove Lakes RR#, St. Address, Box # : 909 North Maize Road City, State, ZIP Code : Wichita, Kansas 67212 Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 9-22-84 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11 in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No xx; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes xx No			
5 TYPE OF BLANK CASING USED: 1 Steel 2 RMP (SB) 3 Wrought iron 4 Concrete tile CASING JOINTS: Glued xx Clamped 2 PVC 4 ABS 5 55 in. to 55 ft., Dia 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Cer-Mac styren SDR-26 Threaded Blank casing diameter 5 in. to 55 ft., Dia 6 Asbestos-Cement 9 Other (specify below) Welded Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. 203 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 55 ft. to 95 ft., From ft. to ft. GRAVEL PACK INTERVALS: From 14 ft. to 95 ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 14 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? None Apparent					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG 0 3 Topsoil 3 8 Clay 8 35 Fine Sand 35 40 Clay 40 95 Medium Sand					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-22-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-16-85 under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					