

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Seelye</u>	<u>SE 1/4 NW 1/4 NW 1/4</u>	<u>19</u>	T <u>27</u> S	R <u>1</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Application Number:
City, State, ZIP Code:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>47</u> ft. ELEVATION: <u>71.80</u>
	Depth(s) Groundwater Encountered <u>20</u> ft. 2. <u>20</u> ft. 3. <u>81.59</u> ft. WELL'S STATIC WATER LEVEL <u>20</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was <u>40</u> ft. after <u>47</u> hours pumping <u>40</u> gpm Est. Yield <u>40</u> gpm: Well water was <u>47</u> ft. after <u>47</u> hours pumping <u>40</u> gpm Bore Hole Diameter <u>14</u> in. to <u>47</u> ft., and <u>47</u> in. to <u>47</u> ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes <u>X</u> No <u>X</u> If yes, mo/day/yr sample was submitted <u>47</u> Water Well Disinfected? Yes <u>X</u> No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped <u>X</u>
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter <u>5</u> in. to <u>37</u> ft., Dia <u>2</u> in. to <u>6</u> in. to <u>47</u> ft., Dia <u>47</u> in. to <u>47</u> ft.			
Casing height above land surface <u>12</u> in., weight <u>2</u> lbs./ft. Wall thickness or gauge No. <u>SPX 4</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From <u>27</u> ft. to <u>47</u> ft., From <u>47</u> ft. to <u>47</u> ft.			
GRAVEL PACK INTERVALS:			
From <u>20</u> ft. to <u>47</u> ft., From <u>47</u> ft. to <u>47</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From <u>2</u> ft. to <u>20</u> ft., From <u>20</u> ft. to <u>47</u> ft., From <u>47</u> ft. to <u>47</u> ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>W</u>				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>8</u>	<u>2</u>	<u>TOP SOIL</u>			
<u>2</u>	<u>18</u>	<u>CLAY</u>			
<u>18</u>	<u>29</u>	<u>MED SAND</u>			
<u>29</u>	<u>47</u>	<u>COARSE</u>			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, <u>(2)</u> reconstructed, or <u>(3)</u> plugged under my jurisdiction and was completed on (mo/day/year) <u>8-15-91</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>RE 463</u> This Water Well Record was completed on (mo/day/yr) <u>8-29-91</u> under the business name of <u>RE 463</u> by (signature) <u>David P. Smith</u>
--