

1 LOCATION OF WATER WELL: County: Sedgwick, Fraction: NE 1/4 NW 1/4 SE 1/4, Section Number: 19, Township Number: 27, Range Number: 1. Distance and direction from nearest town or city street address of well if located within city? See Below, 20.

2 WATER WELL OWNER: GENE THOMAS, 128 N. BYRON RD, WICHITA, KS 67212. Board of Agriculture, Division of Water Resources. Application Number: 7-11-91.

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Section box diagram with X in SE corner]

4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 29 ft. below land surface. WELL'S STATIC WATER LEVEL: 29 ft. below land surface measured on mo/day/yr 7-11-91. Pump test data: Well water was 29 ft. after 1/2 hours pumping 20 gpm. Est. Yield: 60 gpm. Well water was 29 ft. after 1/2 hours pumping 20 gpm. Bore Hole Diameter: 11 in. to 80 ft. and 80 in. to ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Monitoring well. Was a chemical/bacteriological sample submitted to Department? Yes No X. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes X No.

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 5 Wrought iron, 8 Concrete tile, CASING JOINTS: Glued X, Clamped. 2 PVC, 4 ABS, 6 Asbestos-Cement, 9 Other (specify below), Welded. Blank casing diameter: 5 in. to 74 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 12 in. weight: 2-60 lbs./ft. Wall thickness or gauge No. P160. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 11 Other (specify), 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 74 ft. to 80 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 23 ft. to 80 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? South. How many feet? 40.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-18-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318. This Water Well Record was completed on (mo/day/yr) 7-19-91 under the business name of Wings Out by (signature).

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.