


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	19	T 27 S	R 1
Distance and direction from nearest town or city street address of well if located within city?				52895011	
223' NNW from the Intersection of Maple Street and Maize Road, Wichita, KS				Amoco No. 2386 MW-6	
2 WATER WELL OWNER: Groundwater Management Company, Amoco Oil Company					
RR#, St. Address, Box # : 7201 E. 38th Street, Space 7253				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Tulsa, OK 74145				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17 ft. ELEVATION: Approx. Surface Elev.: 1320			
		Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 12.7 ft. below land surface measured on mo/day/yr 04/04/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 17.5 ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel		5 Wrought iron	8 Concrete tile	Welded	
2 PVC		6 Asbestos-Cement	9 Other (specify below)	Threaded X	
3 RMP (SR)		7 Fiberglass			
4 ABS					
Blank casing diameter 2 in. to 7 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface -2 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel		5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	
2 Brass		6 Concrete tile	9 ABS	11 Other (specify)	
3 Stainless steel		12 None used (open hole)			
4 Galvanized steel					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		6 Wire wrapped	8 Saw cut	11 None (open hole)	
2 Louvered shutter		7 Torch cut	9 Drilled holes		
3 Mill slot		10 Other (specify)			
4 Key punched					
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 6 ft. to 17.5 ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement			
Grout Intervals: From 0 ft. to 4 ft., From 4 ft. to 6 ft., From ft. to ft.		2 Cement grout			
What is the nearest source of possible contamination:		3 Bentonite			
1 Septic tank		7 Pit privy	10 Livestock pens	14 Abandoned water well	
2 Sewer lines		8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well	
3 Watertight sewer lines		9 Feedyard	12 Fertilizer storage	16 Other (specify below)	
4 Lateral lines		13 Insecticide storage			
5 Cess pool		How many feet? 141			
6 Seepage pit					
Direction from well? SW					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4.5	Brown Lean Silty Clay			
4.5	8.5	Red-Brown Clayey Sand			
8.5	12	Olive-Brown to Olive-Gray Lean Sandy Clay			
12	17.5	Olive-Gray Fine to Coarse Clayey Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/01/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 04/29/89 under the business name of Terracon Consultants, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					