

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number																																																													
County: Sedgwick		SE 1/4		SE 1/4		19		T 27 S R 1 EWP																																																													
Distance and direction from nearest town or city street address of well if located within city?																																																																					
90' N of NW corner of Maple and Malze; Wichita, KS Amoco #2386 50885087 MW-2																																																																					
2 WATER WELL OWNER: Groundwater Management Section, Amoco Corporation																																																																					
RR#, St. Address, Box # : 4502 East 41st Street					Board of Agriculture, Division of Water Resources																																																																
City, State, ZIP Code : Tulsa, OK 74135					Application Number:																																																																
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 18 ft. ELEVATION: Approx. Surface Elev.: 100.5																																																																			
		Depth(s) Groundwater Encountered 1 12 ft. 2 ft. 3 ft.																																																																			
		WELL'S STATIC WATER LEVEL 11.2 ft. below land surface measured on mo/day/yr 7/18/88																																																																			
		Pump test data: Well water was ft. after hours pumping gpm																																																																			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm																																																																			
		Bore Hole Diameter 7 in. to 18 ft., and in. to ft.																																																																			
WELL WATER TO BE USED AS:																																																																					
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																																																																					
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted																																																																					
Water Well Disinfected? Yes No X																																																																					
5 TYPE OF BLANK CASING USED:																																																																					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X																																																																					
Blank casing diameter 2 in. to 18 ft., Dia in. to ft., Dia in. to ft.																																																																					
Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No.																																																																					
TYPE OF SCREEN OR PERFORATION MATERIAL:																																																																					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)																																																																					
SCREEN OR PERFORATION OPENINGS ARE:																																																																					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes																																																																					
SCREEN-PERFORATED INTERVALS: From 8 ft. to 18 ft., From ft. to ft.																																																																					
GRAVEL PACK INTERVALS: From 6.5 ft. to 18 ft., From ft. to ft.																																																																					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																																																					
Grout Intervals: From 4.5 ft. to 6.5 ft., From ft. to ft., From ft. to ft.																																																																					
What is the nearest source of possible contamination:																																																																					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage																																																																					
Direction from well? East How many feet? 250																																																																					
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">FROM</th> <th colspan="2">TO</th> <th>LITHOLOGIC LOG</th> <th colspan="2">FROM</th> <th colspan="2">TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>4</td> <td colspan="3">Dark Brown to Gray-Brown Lean to Fat Clay</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>6.5</td> <td colspan="3">Red-Brown Sandy Lean Clay</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>6.5</td> <td>10</td> <td colspan="3">Gray With Red-Brown Clayey Fine to Medium Sand</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>15</td> <td colspan="3">Gray-Brown Fine to Medium Sand, Trace Silt</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>18</td> <td colspan="3">Brown Fine to Coarse Sand, Trace Silt</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>										FROM		TO		LITHOLOGIC LOG	FROM		TO		PLUGGING INTERVALS	0	4	Dark Brown to Gray-Brown Lean to Fat Clay								4	6.5	Red-Brown Sandy Lean Clay								6.5	10	Gray With Red-Brown Clayey Fine to Medium Sand								10	15	Gray-Brown Fine to Medium Sand, Trace Silt								15	18	Brown Fine to Coarse Sand, Trace Silt							
FROM		TO		LITHOLOGIC LOG	FROM		TO		PLUGGING INTERVALS																																																												
0	4	Dark Brown to Gray-Brown Lean to Fat Clay																																																																			
4	6.5	Red-Brown Sandy Lean Clay																																																																			
6.5	10	Gray With Red-Brown Clayey Fine to Medium Sand																																																																			
10	15	Gray-Brown Fine to Medium Sand, Trace Silt																																																																			
15	18	Brown Fine to Coarse Sand, Trace Silt																																																																			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/12/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 10-10-88 under the business name of Tantacon Consultants Inc by (signature) J. E. E.																																																																					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.																																																																					