

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		SE 1/4 SE 1/4 SE 1/4	19	T 27 S	R 1 E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city?				52895011	
177' WNW from the Intersection of Maple Street and Maize Road, Wichita, KS				Amoco No. 2386 MW-4	
2 WATER WELL OWNER: Groundwater Management Company, Amoco Oil Company					
RR#, St. Address, Box # : 7201 E. 38th Street, Space 7253				Board of Agriculture, Division of Water Resources	
City, State, ZIP Code : Tulsa, OK 74145				Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 17 ft. ELEVATION: Approx. Surface Elev: 1320			
N 1 Mile W E S X		Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 13.5 ft. below land surface measured on mo/day/yr 04/04/89			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield N/A gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 17.5 ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded. X			
Blank casing diameter 2 in. to 7 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface -2 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 5 ft. to 17.5 ft., From ft. to ft.					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	5	Brown Lean Silty Clay			
5	9.5	Light Brown Fine to Medium Clayey Sand			
9.5	13	Red-Brown Medium Sand, Trace Clay			
13	17.5	Brown Medium to Coarse Sand			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 5 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? NW How many feet? 6					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 04/01/89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1/24/89 under the business name of Terracon Consultants, Inc. by (signature) <i>[Signature]</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					