

LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK 173		NE ¼ SW ¼ SW ¼	19	T 27 S	R 1W EW
Distance and direction from nearest town or city street address of well if located within city?					
11603 West Texas Wichita, Kansas					
WATER WELL OWNER:		Town & Country Plbg.		Spec. Home	
RR#, St. Address, Box # :		11603 West Texas		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code :		Wichita, Kansas		Application Number: /	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		DEPTH OF COMPLETED WELL: 115 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 28 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 28 ft. below land surface measured on mo/day/yr 7-10-84 ✓			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 1.15 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
TYPE OF BLANK CASING USED:		CASING JOINTS:			
1 Steel 3 RMP (SR)		Glued X Clamped			
2 PVC 4 ABS		Welded			
		Threaded			
Blank casing diameter . . . 5 in. to .95 ft., Dia . . . in. to ft., Dia . . . in. to ft.		5 Wrought iron 8 Concrete tile			
Casing height above land surface . . . 12 in., weight . . . 1.59 lbs./ft. Wall thickness or gauge No. . . 203		6 Asbestos-Cement 9 Other (specify below)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		Cer-Mac Styrene SDR-26			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		10 Asbestos-cement			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut		11 Other (specify)			
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From . . . 95 ft. to . . . 115 ft., From . . . ft. to . . . ft.		10 Other (specify)			
GRAVEL PACK INTERVALS: From . . . 14 ft. to . . . 115 ft., From . . . ft. to . . . ft.					
FROM . . . ft. to . . . ft., FROM . . . ft. to . . . ft.					
GROUT MATERIAL:		Grout Intervals:			
1 Neat cement 2 Cement grout 3 Bentonite 4 Other		From . . . 4 ft. to . . . 14 ft., From . . . ft. to . . . ft., From . . . ft. to . . . ft.			
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well? East		How many feet? 31			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	28 01	Clay			
28	45 08	Medium Sand			
45	90 01	Clay			
90	115				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-10-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 10-31-84 under the business name of Harp Well & Pump Service, INC. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					