

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>		<u>SW</u> 1/4 <u>SW</u> 1/4 <u>SW</u> 1/4	<u>19</u>	<u>T 27 S</u>	<u>R 1 W E/W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>228 So. Pinegrove</u> <u>Wichita, Ks.</u>					
2 WATER WELL OWNER: <u>Stan Deree</u> RR#, St. Address, Box # : <u>228 So. Pinegrove</u> City, State, ZIP Code : <u>Wichita, Ks.</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>80</u> ft. ELEVATION:			
N W E SW SE X		Depth(s) Groundwater Encountered 1. <u>28</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr <u>5-16-85</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter. <u>11</u> in. to ft., and in. to ft.			
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <u>X</u> Clamped			
1 Steel 3 <u>RMP (SR)</u>		6 Asbestos-Cement 9 Other (specify below) Welded			
2 PVC 4 <u>ABS</u>		7 Fiberglass <u>Cer-Mac styrene SDR-26</u> Threaded			
Blank casing diameter in. to <u>60</u> ft., Dia in. to ft., Dia in. to ft.		Casing height above land surface. <u>12</u> in., weight <u>1.59</u> lbs./ft. Wall thickness or gauge No. <u>203</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 <u>RMP (SR)</u> 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>60</u> ft. to <u>80</u> ft., From ft. to ft.		GRAVEL PACK INTERVALS: From <u>14</u> ft. to <u>80</u> ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other		Grout Intervals: From <u>4</u> ft. to <u>14</u> ft., From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 <u>Watertight sewer lines</u> 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? <u>North</u> How many feet? <u>50</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	39	Clay			
39	50	Fine Sand			
50	80	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-16-85</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) <u>6-8-85</u> under the business name of <u>Harp Well & Pump Service, Inc.</u> by (signature) <u>Mary Arnold</u>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					