

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County:	Sedgwick	SE 1/4 NW 1/4 SE 1/4	19	T 27 S	R 1 E

Distance and direction from nearest town or city street address of well if located within city?

See Below.

2 WATER WELL OWNER: Brian Knapp
RR#, St. Address, Box # : 219 N. Karen
City, State, ZIP Code : WICHITA KS 67212

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 96 ft. ELEVATION: 222

Depth(s) Groundwater Encountered _____ ft. _____ ft. _____ ft.

WELL'S STATIC WATER LEVEL _____ ft. below land surface measured on mo/day/yr 5-4-94

Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm

Est. Yield 30 gpm: Well water was _____ ft. after _____ hours pumping _____ gpm

Bore Hole Diameter 11 in. to 96 ft. and _____ in. to _____ ft.

WELL WATER TO BE USED AS:

1 Domestic	3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation	4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		<u>7 Lawn and garden only</u>	10 Monitoring well	

Was a chemical/bacteriological sample submitted to Department? Yes _____ No X; If yes, mo/day/yr sample was submitted _____

Water Well Disinfected? Yes X No _____

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued ☒ Clamped ☐
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded ☐
		7 Fiberglass		Threaded ☐

Blank casing diameter 5 in. to 86 ft., Dia 5 in. to 86 ft., Dia 5 in. to 86 ft.

Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 86 ft. to 96 ft., From 86 ft. to 96 ft., From 86 ft. to 96 ft.

GRAVEL PACK INTERVALS: From 23 ft. to 96 ft., From 23 ft. to 96 ft., From 23 ft. to 96 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 3 ft. to 23 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? west How many feet? 25

FROM		TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2		Top so. /			
2	12		clay.			
12	47		fine sand.			
47	79		clay.			
79	96		med sand.			

7. CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-4-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-5-94 under the business name of Weninger Dull by (signature) [Signature]