


1 LOCATION OF WATER WELL: Fraction SE 1/4 NE 1/4 NW 1/4 Section Number 20 Township Number T 27 S Range Number R 1 E
 County: Seelye
 Distance and direction from nearest town or city street address of well if located within city?
See Below.

2 WATER WELL OWNER: Ray Duling
 RR#, St. Address, Box #: 9300 W. SHADE
 City, State, ZIP Code: WICHITA KS 67212
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 26 ft. 2. 26 ft. 3. 5-3-94 ft.
 WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 5-3-94
 Pump test data: Well water was 26 ft. after 20 hours pumping 20 gpm
 Est. Yield 30 gpm: Well water was 26 ft. after 20 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 80 ft., and 80 in. to 80 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 70 ft. Dia. 70 in. to 70 ft. Dia. 70 in. to 70 ft. Dia. 70 in. to 70 ft. Dia.
 Casing height above land surface 12 in. weight 2.60 lbs./ft. Wall thickness or gauge No. 160PVC
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 70 ft. to 80 ft. From 70 ft. to 80 ft. From 70 ft. to 80 ft. From 70 ft. to 80 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 80 ft. From 23 ft. to 80 ft. From 23 ft. to 80 ft. From 23 ft. to 80 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 80 ft. From 80 ft. to 80 ft. From 80 ft. to 80 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? EAST How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top soi			
2	17	clay			
17	42	fine sand			
42	43	clay			
43	80	fine to med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-3-94 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 6-25-94
 under the business name of Weninger Duling by (signature) Garner