

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		SW 1/4 SE 1/4 SE 1/4	20	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? SEE BELOW					
2 WATER WELL OWNER: MI SEDDON					
RR#, St. Address, Box # : 147 S. BYRON RD.					
City, State, ZIP Code : WICHITA KS 67209					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 96 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 35 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL 35 ft. below land surface measured on mo/day/yr 3-20-92			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm			
		Bore Hole Diameter . in. to . ft., and . in. to . ft.			
WELL WATER TO BE USED AS:					
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below) ☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well					
Was a chemical/bacteriological sample submitted to Department? Yes. . No. ☒ If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes ☒ No					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped . ☒ 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded . Blank casing diameter 5 in. to 90 ft. Dia . in. to . ft. Dia . in. to . ft. Casing height above land surface 18 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 160 PVC TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 90 ft. to 96 ft., From . ft. to . ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 23 ft. to 96 ft., From . ft. to . ft., From . ft. to . ft.					
6 GROUT MATERIAL:					
1 Neat cement ☒ 2 Cement grout 3 Bentonite 4 Other . Grout Intervals: From 3 ft. to 23 ft., From . ft. to . ft., From . ft. to . ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? West How many feet? 65					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil	88	89	clay
2	18	clay	89	96	med. gravel
18	30	fine sand			
30	33	clay			
33	60	med to fine sand			
60	62	clay			
62	88	fine sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-20-92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 3-23-92 under the business name of Weninger Drilling, Inc. by (signature) Susan T. Weninger					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					