

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Sedgwick		SE 1/4 NE 1/4 SE 1/4		20		T 27 S		R 1W	
Distance and direction from nearest town or city street address of well if located within city?									
134 Wood Wichita, Ks.									
2 WATER WELL OWNER:		Jim Loney		Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box # :		134 Wood		Application Number:					
City, State, ZIP Code :		Wichita, Ks.							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:							
N		Depth(s) Groundwater Encountered 1. 25 ft. 2. ft. 3. ft.							
W		WELL'S STATIC WATER LEVEL 25 ft. below land surface measured on mo/day/yr 6-7-89							
1 Mile		Pump test data: Well water was ft. after hours pumping gpm							
E		Est. Yield gpm: Well water was ft. after hours pumping gpm							
S		Bore Hole Diameter 11 in. to 80 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued X Clamped			
1 Steel		3 RMP (SR)		6 Asbestos-Cement		Welded			
2 PVC		4 ABS		7 Fiberglass		Cer-Mac styrene SDR-26 Threaded			
Blank casing diameter 5 in. to 60 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement					
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)			
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)			
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes			
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 60 ft. to 80 ft. From ft. to ft.							
GRAVEL PACK INTERVALS:		From 24 ft. to 80 ft. From ft. to ft.							
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite		4 Other	
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens		14 Abandoned water well					
1 Septic tank		4 Lateral lines		7 Pit privy		11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines		5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		13 Insecticide storage			
Direction from well? East		How many feet? 100							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 topsoil									
3 17 clay									
17 32 fine sand									
32 44 medium sand									
44 51 clay									
51 59 fine sand									
59 80 medium sand									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-7-89 and this record is true to the best of my knowledge and belief, Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 7-20-89 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.									