


1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 NE 1/4 Section Number 20 Township Number T 27 S Range Number R 1 EW
 County: Sedgwick Distance and direction from nearest town or city street address of well if located within city? See Below

2 WATER WELL OWNER: Mark TAIBERT 170 N. BRYON Rd Wichita KS 67212
 RR#, St. Address, Box # : Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION: 2838 ft.
 Depth(s) Groundwater Encountered 1. 2838 ft. 2. 28 ft. 3. 6-8-87 ft.
 WELL'S STATIC WATER LEVEL 2838 ft. below land surface measured on 6-8-87 mo/day/yr
 Pump test data: Well water was 28 ft. after 12 hours pumping 20 gpm
 Est. Yield 50 gpm: Well water was 28 ft. after 12 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 55 ft. and 55 in. to 55 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
 7 Fiberglass
 Blank casing diameter 5 in. to 45 ft. Dia 159 lbs./ft. Wall thickness or gauge No SDR-26
 Casing height above land surface 12 in. weight 159 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 45 ft. to 55 ft. From 45 ft. to 55 ft.
 GRAVEL PACK INTERVALS: From 23 ft. to 55 ft. From 23 ft. to 55 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 3 ft. to 23 ft. From 23 ft. to 55 ft. From 55 ft. to 55 ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? South How many feet? 40

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	22	clay			
22	34	fine sand			
34	25	clay			
35	55	med sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-87 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. 6318 This Water Well Record was completed on (mo/day/yr) 6-9-87
 under the business name of Weninger Drill by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4