

1 LOCATION OF WATER WELL: County: Sedg. Fraction: 8 1/4 Sec 1/4 NW 1/4 Section Number: 21 Township Number: T. 27 S Range Number: R. 1 E/W. Distance and direction from nearest town or city street address of well if located within city? 258 Glenn Eagles Wichita

2 WATER WELL OWNER: RR#, St. Address, Box #: Westwood Const 1825 No Cramer City, State, ZIP Code: Wichita KS 67212 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the center section (16) and 'o' in the bottom center section (30).] 4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 425.85 ft. Depth(s) Groundwater Encountered: 1. 24 ft. 2. 26 ft. 3. 20 ft. WELL'S STATIC WATER LEVEL: 24 ft. below land surface measured on mo/day/yr Pump test data: Well water was 40 gpm; Well water was 26 ft. after 12 hours pumping 20 gpm. Est. Yield: 40 gpm; Well water was 26 ft. after 12 hours pumping 20 gpm. Bore Hole Diameter: 11 in. to 6.5 ft., and 6.5 in. to 11 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 12 Other (Specify below). 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below). 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well. Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes. No. X

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 5.5 ft., Dia. 1.59 in. to 1.59 ft., Dia. Casing height above land surface: 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SDR 26. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-cement, 11 Other (specify), 12 None used (open hole). 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS. SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole). 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes. SCREEN-PERFORATED INTERVALS: From 55 ft. to 65 ft., From 55 ft. to 65 ft., From 55 ft. to 65 ft., From 55 ft. to 65 ft. GRAVEL PACK INTERVALS: From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft., From 13 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft., From 3 ft. to 13 ft. What is the nearest source of possible contamination: 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Water right sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? North. How many feet? 40.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-25-85 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318. This Water Well Record was completed on (mo/day/yr) 4-25-85 under the business name of Weninger Drilling by (signature) Weninger.

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.