


1 LOCATION OF WATER WELL:		Fraction <u>SW SW</u>	Section Number <u>22 27</u>	Township Number <u>T 27 S</u>	Range Number <u>R 1 W 1E W</u>
County: <u>SEDGWICK</u>					
Distance and direction from nearest town or city street address of well if located within city? <u>453 S. Summitlawn, Wichita, Ks.</u>					
2 WATER WELL OWNER: <u>Mr. Horn</u>		RR#, St. Address, Box #: <u>453 S. Summitlawn</u>			
City, State, ZIP Code: <u>Wichita, Ks.</u>		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>84</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1</u> <u>25</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>25</u> ft. below land surface measured on mo/day/yr <u>8-12-82</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
Bore Hole Diameter <u>11</u> in. to ft., and in. to ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Observation well	
Was a chemical/bacteriological sample submitted to Department? Yes.....No <u>X</u>; If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes <u>X</u> No					
5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped	
1 Steel		3 RMP (SR)	6 Asbestos-Cement	Welded	
2 PVC		4 ABS	7 Fiberglass	Threaded	
Blank casing diameter 5 in. to <u>64</u> in. Dia. in. to ft. Dia. in. to ft.		Cer-Mac Styrene SDR-26			
Casing height above land surface 12 in. weight <u>1.59</u> lbs./ft. Wall thickness of gauge No. <u>203</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC	10 Asbestos-cement		
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 64 ft. to 84 ft.	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:		From 14 ft. to 84 ft.	From ft. to ft.	From ft. to ft.	
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4 ft. to 14 ft.		From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well		
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>Northeast</u>		How many feet? <u>88</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	12	Clay			
12	33	Fine Sand			
33	41	Clay			
41	63	Medium (Dirty) Sand			
63	80	Medium Sand			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-12-82</u> and this record is true to the best of my knowledge and belief Kansas Water Well Contractor's License No. <u>236</u> This Water Well Record was completed on (mo/day/yr) <u>10-18-82</u> under the business name of <u>Harp Well & Pump Serv., Inc.</u> by (signature) <u>M. Arnold</u>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					