

1 LOCATION OF WATER WELL: Fraction NW 1/4 SE 1/4 SE 1/4 Section Number 23 Township Number 27 S Range Number 1 E/W 0
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city? 129 Nevada Wichita KS.

2 WATER WELL OWNER: Gaylen Longhoffer
RR#, St. Address, Box #: 10100 W. Maple
City, State, ZIP Code: Wichita KS 67209
Board of Agriculture, Division of Water Resources
Application Number: 30

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 16 ft.

Depth(s) Groundwater Encountered 1. 16 ft. 2. 16 ft. 3. 16 ft.
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 16 ft. after 16 hours pumping 16 gpm
Est. Yield 16 gpm: Well water was 16 ft. after 16 hours pumping 16 gpm
Bore Hole Diameter 16 in. to 16 ft., and 16 in. to 16 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes 16 No 16; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes 16 No 16

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 16 Clamped 16
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 16
Blank casing diameter 16 in. to 16 ft., Dia. 16 in. to 16 ft., Dia. 16 in. to 16 ft.
Casing height above land surface 16 ft. below 16 ft. weight 16 lbs./ft. Wall thickness or gauge No. 16
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 16
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 16

SCREEN-PERFORATED INTERVALS: From 16 ft. to 16 ft., From 16 ft. to 16 ft., From 16 ft. to 16 ft.
GRAVEL PACK INTERVALS: From 16 ft. to 16 ft., From 16 ft. to 16 ft., From 16 ft. to 16 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 16
Grout Intervals: From 16 ft. to 16 ft., From 16 ft. to 16 ft., From 16 ft. to 16 ft.
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16

Direction from well? South
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0 3 top soil
3 16 cement
16 30 sand + gravel

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-11-93 and this record is true to the best of my knowledge and belief, Kansas
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 3-15-93
under the business name of Weninger Drilling Inc by (signature) Susan Weninger