

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number				
County: <u>Sedgwick</u>		NW 1/4 SE 1/4 SE 1/4	23	T 27 S	R 1W EW				
Distance and direction from nearest town or city street address of well if located within city?									
122 S. Nevada Wichita, Ks.									
2 WATER WELL OWNER: Mid-Kansas Federal Savings & Loan									
RR#, St. Address, Box # : 230 S. Market Board of Agriculture, Division of Water Resources									
City, State, ZIP Code : Wichita, Ks. Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION:							
N 1 Mile W E S <table border="1" style="margin: auto; text-align: center;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE X</td></tr></table>		NW	NE	SW	SE X	Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.			
		NW	NE						
		SW	SE X						
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 10-17-89							
		Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter 11 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)		5 Public water supply 8 Air conditioning 11 Injection well							
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 <u>BMP (SR)</u> 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 30 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 12 in. weight 1.59 lbs./ft. Wall thickness or gauge No. 203									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 <u>BMP (SR)</u> 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 24 ft. to 40 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 <u>Cement grout</u> 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? <u>East</u> How many feet? 80									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	3	topsoil							
3	11	clay							
11	17	fine sand							
17	40	medium sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-17-89 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 4-30-90									
under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold									