


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

218 N. Kessler SE NE NW SW

1. Location of well:	County SEDGWICK	Fraction SW 1/4 SW 1/4 SW 1/4	Section number 24	Township number T 27 S R 1 E	Range number 1
2. Distance and direction from nearest town or city:	3. Owner of well: REVA GUERRA R.R. or street: 2616 BOB WHITE City, state, zip code: WICHITA KS 67204				
4. Locate with "X" in section below:	Sketch map: BORED 9" HOLE TO 13' THEN 6" TO 21' SET CASING & COMPLETED WITH SAND BUCKET				
					
5. Type and color of material	From	To	6. Bore hole dia. 9 in. Completion date 12-18-79 Well depth 38 ft. GRADE		
DARK SANDY SOIL	0	3	7. Cable tool ☐ Rotary ☐ Driven ☐ Dug ☐ ☐ Hollow rod ☐ Jetted ☒ Bored ☐ Reverse rotary		
SANDY SUB SUIC	3	5	8. Use: ☒ Domestic ☐ Public supply ☐ Industry ☐ Irrigation ☐ Air conditioning ☐ Stock ☐ Lawn ☐ Oil field water ☐ Other		
CLAY GRASS	5	6	9. Casing: Material RMP Height: Above or below Threading: ☒ Welded ☐ Surface 12 in. RMP 5 PVC 39 Weight 133 lbs./ft. Dia. 5 in. to 39 ft. depth Wall Thickness: inches or Dia. 5 in. to 39 ft. depth gage No. 0.200		
SAND TAN FINE	6	12	10. Screen: Manufacturer's name SUNFLOWER Type RMP Dia. 5 INCH Slot/gauze 0.31 Length 7 FT. Set between 31 ft. and 38 ft. ft. and 38 ft. Gravel pack? NO Size range of material		
CLAY BROWN	12	14	11. Static water level: 21 ft. below land surface Date 12-18-79 mo./day/yr.		
SAND TAN FINE	14	20	12. Pumping level below land surfaces: ft. after NA hrs. pumping NA g.p.m. ft. after NA hrs. pumping NA g.p.m. Estimated maximum yield 75 g.p.m.		
CLAY GRAY	20	21	13. Water sample submitted: NO mo./day/yr. Yes ☒ No ☐ Date		
SAND COARSE GRAY	21	24	14. Well head completion: 12 inches above grade ☒ Pitless adapter		
SAND COARSE	21	38	15. Well grouted? YES With: ☐ Neat cement ☐ Bentonite ☒ Concrete Depth: From 3 ft. to 13 ft.		
(Use a second sheet if needed)			16. Nearest source of possible contamination: PLASTIC ft. 15 Direction N. Type SEWER Well disinfected upon completion? ☒ Yes ☐ No		
18. Elevation: 1300'			17. Pump: Not installed Manufacturer's name FTW Model number 50A8 HP .50 Volts 230 Length of drop pipe 30 ft. capacity 10 g.p.m. Type: ☒ Submersible ☐ Turbine ☐ Jet ☐ Reciprocating ☐ Centrifugal ☐ Other		
19. Remarks:			20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN Pump & Well Business name BEARDEN License No. 1014 Address 2142 MENTOR WICHITA Signed Otis W. Bearden Date 1-20-80 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5