


1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SW 1/4 Section Number 24 Township Number 27 Range Number 0
County: Sedgwick
Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Melinda Brand
RR#, St. Address, Box #: 214 S. McComas
City, State, ZIP Code: White KS 67213
Board of Agriculture, Division of Water Resources
Application Number: 30

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 15 ft. 2. 30 ft. 3. 30 ft.
WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 30 ft. after 30 hours pumping 30 gpm
Est. Yield 30 gpm: Well water was 30 ft. after 30 hours pumping 30 gpm
Bore Hole Diameter 30 in. to 30 ft., and 30 in. to 30 ft.
WELL WATER TO BE USED AS:
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well abandoned
Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
Blank casing diameter 1 1/4 in. to 30 ft. Dia. 30 in. to 30 ft. Dia. 30 in. to 30 ft. Dia. 30 in. to 30 ft. Dia.
Casing height above land surface 30 ft. Wall thickness or gauge No. 30
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement NA
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) NA
2 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
7 Torus cut
SCREEN-PERFORATED INTERVALS: From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft.
GRAVEL PACK INTERVALS: From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft. From 30 ft. to 30 ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
Direction from well? West
How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			30	8	cement grout
					Well in basement
					2 wells side by side
					Sand point

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-31-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-31-93 under the business name of Weninger Drilling Inc. by (signature) Susan Weninger