

1 LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>25</u>	Township Number T <u>27</u> S	Range Number R <u>1</u> EW
--	---	-----------------------------	----------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

In Town

2 WATER WELL OWNER: <u>ANR Freight</u> RR#, St. Address, Box # : <u>3402 W. Harry</u> City, State, ZIP Code : <u>Wichita, KS</u>	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>20 ft.</u> ELEVATION:
--	--

Depth(s) Groundwater Encountered 1. 14 ft. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL 13.71 ft. below land surface measured on mo/day/yr 9-9-92

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm Well water was ft. after hours pumping gpm

Bore Hole Diameter 6 5/8 in. to 20 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
------------------------------	----------------	-----------------	------------------------------

1 Steel

2 PVC

3 RMP (SR)

4 ABS

Blank casing diameter 2.38 in. to 10 ft. Dia. in. to ft. Dia. in. to ft.

Casing height above land surface Flush Mount in., weight lbs./ft. Wall thickness or gauge No. SDR-13 Sch 40

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)

7 Fiberglass

7 PVC

10 Asbestos-cement

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot .010	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 20 ft. to 10 ft. From ft. to ft. From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 9 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
-------------------	---------------	----------------	-------------	---------

Grout Intervals: From 9 ft. to 2 ft. From 2 ft. to 0 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? South How many feet? 140 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	Asphalt w/ brown silty gravelly fill			
1.5	4.5	Brown sandy silt			
4.5	7.5	Brown mottled silty clay			
7.5	10.0	Gray-Dk Gray silty clay w/ iron oxide staining			
10.0	14.0	Brown mottled clay w/ iron oxides			
14.0	20.0	Fine to coarse grain sand & gravel subangular-sub rounded, poorly sorted			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-9-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>9-12-92</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Bueh</u>
--