

MW-6D 1911010

WATER WELL RECORD Form WWC-5 KSA 82a-1212


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Sedgwick	NE 1/4 SW 1/4 SE 1/4	25	T 27 S	R 1 EW

Distance and direction from nearest town or city street address of well if located within city?

1539 S. St. Paul

2 WATER WELL OWNER:	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #:	Application Number:
City, State, ZIP Code:	

Globe Engineering
1539 S. St. Paul
Wichita KS 67213

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 55.9 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 5.9 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 8.48 ft. below land surface measured on mo/day/yr 5-4-93
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8 in. to ft. and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded Flush
Blank casing diameter 2 in. to ft. Dia			
Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel		11 Other (specify)
12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 45 ft. to 55 ft.		
GRAVEL PACK INTERVALS:	From 44 ft. to 55 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 1 ft. to 44 ft.			
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? NA				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				NA
				How many feet? NA

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	2.0	Silt, dark brown, Clayey			
2.0	5.5	Silt, light gray, sandy			
2.0	5.5	Clay, light brown, very silty			
5.5	12.0	Silt, light gray, sandy			
12.0	21.0	Sand, light brown, coarse to very coarse			
21.0	35.0	Sand, tan, very coarse & gravel			
35.0	51.0	Sand, white to light tan, fine to med. grain			
51.0	55.0	Shale, slightly weathered, dark gray			
		Flush Mount waiver granted 12-10-92			
		for Globe Engineering by Don Taylor			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-4-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 5-13-93 under the business name of GSI by (signature) Allen Swain

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.