

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedgwick</u>	<u>SE 1/4 SW 1/4 SE 1/4</u>	<u>25</u>	T <u>27</u> S	R <u>1</u> EW

Distance and direction from nearest town or city street address of well if located within city?

1539 S. St. Paul

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
	<u>Globe Engineering</u>	<u>1539 S. St. Paul</u>	
	<u>Wichita KS 67213</u>		Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>25</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered <u>10.3</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>7.98</u> ft. below land surface measured on <u>mo/day/yr</u> <u>5-4-93</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>2 PVC</u>	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>2</u> in. to ft. Dia			<u>Threaded</u> <u>Flush</u>
Casing height above land surface <u>Flush</u> in. weight <u>703</u> lbs./ft. Wall thickness or gauge No. <u>154</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 Other (specify)
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel	5 Gauzed wrapped	8 Saw cut
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	<u>3 Mill slot</u>	6 Wire wrapped
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>5</u> ft. to <u>25</u> ft.	From ft. to ft.	From ft. to ft.
GRAVEL PACK INTERVALS:	From <u>4</u> ft. to <u>25</u> ft.	From ft. to ft.	From ft. to ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>3 Bentonite</u>	4 Other
Grout Intervals:	From <u>4</u> ft. to <u>1</u> ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? <u>NA</u>				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				<u>NA</u>
				How many feet? <u>NA</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0.0</u>	<u>3.5</u>	<u>Clay, dark gray, silty</u>			
<u>3.5</u>	<u>6.0</u>	<u>Clay, olive green</u>			
<u>6.0</u>	<u>8.5</u>	<u>Clay, dark gray</u>			
<u>8.5</u>	<u>11.0</u>	<u>Silt, gray</u>			
<u>11.0</u>	<u>13.5</u>	<u>Silt, gray</u>			
<u>13.5</u>	<u>16.0</u>	<u>Sand, gray, fine - med.</u>			
<u>16.0</u>	<u>18.5</u>	<u>Sand, gray, med - coarse</u>			
<u>18.5</u>	<u>21.0</u>	<u>Sand, gray, med - coarse</u>			
<u>21.0</u>	<u>23.5</u>	<u>Sand, tan, med - coarse</u>			
<u>23.5</u>	<u>25.0</u>	<u>Sand, yellow, coarse sand to gravel</u>			
Flush mound waiver granted 12-10-92 for Globe Engineering by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) <u>5-4-93</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>531</u> This Water Well Record was completed on (mo/day/yr) <u>5-13-93</u> under the business name of <u>GSI</u> by (signature) <u>Allen Krueger</u>
