


1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 25	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 1550 S. WEST ST, WICHITA, KS OW-5					
2 WATER WELL OWNER: PMI, INC RR#, St. Address, Box #: 1550 S. WEST ST. City, State, ZIP Code: WICHITA, KS 67218			Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 15.5 ft. ELEVATION: 1299.28 Depth(s) Groundwater Encountered 1. 10 ft. 2. - ft. 3. - ft. WELL'S STATIC WATER LEVEL 10.07 ft. below land surface measured on mo/day/yr 4-24-93 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield - gpm: Well water was - ft. after - hours pumping - gpm Bore Hole Diameter 8 in. to 15.5 ft., and - in. to - ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ 11 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes - No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes - No ☒			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped - ☒ 2 PVC 4 ABS 7 Fiberglass Welded - Threaded ☒ Blank casing diameter 2 in. to 5.5 ft., Dia - in. to - ft., Dia - in. to - ft. Casing height above land surface -3.5 in., weight - lbs./ft. Wall thickness or gauge No. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot ☒ 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 5.5 ft., From - ft. to - ft. GRAVEL PACK INTERVALS: From 15.5 ft. to 4.5 ft., From - ft. to - ft. From - ft. to - ft., From - ft. to - ft.					
6 GROUT MATERIAL: ☒ 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other Grout Intervals: From 4.5 ft. to 0 ft., From - ft. to - ft., From - ft. to - ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy ☒ 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon ☒ 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? SE How many feet? 110					
LITHOLOGIC LOG			PLUGGING INTERVALS		
FROM	TO		FROM	TO	
0	0.7'	GRAVEL			
0.7'	3.0'	DARK BROWN Silty CLAY			
3.0	9.5	GREY BROWN SANDY Silty CLAY			
9.5	14.5	LT. BROWN FINE GRAIN SAND			
14.5	15.5	LT. BROWN & GREY MED COARSE GRAIN SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/23/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 7/1/93 under the business name of Terracon by (signature) Ronald G. Gilllette					